



**AK Rubber & Industrial Supplies Ltd**

SHEETING • MATTING • GASKETS • STRIP • MOULDINGS  
EXTRUSIONS • INDUSTRIAL HOSES • FITTINGS • CLIPS • SEALANTS



18 Twyford Business Centre • London Road • Bishop's Stortford • Herts • CM23 3YT  
email: sales@akrubber.co.uk Tel: 01279 719000 Fax: 01279 719001

**ETHYLENE PROPYLENE (EPDM) RUBBER – PRODUCT DATA**

Grade	Polymer	Colour	Hardness Shore 'A'	Density (g/cm <sup>3</sup> )	Tensile Strength (MPa)	Elongation At Break (%)	Temperature Range (°C)	Description
AK2349	SBR/EPDM	Black	60° ± 5°	1.5 ± 0.05	3.0 Min	250	-20°C to +70°C	CQ EPDM
AK1362	EPDM	Black	70	1.22	9 min	200 min	-15°C to +100°C	BS6920 BS EN681-1 WA70 WRAS Approved for cold water only
AKE80/ECON	SBR/EPDM	Black	70	1.4	3.5	250	-20°C to +110°C	Economy CQ EPDM
AKE80	SBR/EPDM	Black	65	1.4	5	300	-20°C to +110°C	CQ EPDM
AKE80C/M	SBR/EPDM	Black	65	1.4	5	300	-20°C to +110°C	CQ EPDM (Cloth Marked)
AKM117	SBR/EPDM	Black	65	1.4	5	350	-20°C to +100°C	Medium EPDM
AKM145	EPDM	Black	60	1.3	5	350	-30°C to +120°C	High grade EPDM

Standard Roll Sizes:-

Thickness	Width	Length
1.0mm	1400mm	10 Metres
1.5mm	1400mm	10 Metres
2.0mm	1400mm	10 Metres
3.0mm	1400mm	10 Metres
4.0mm	1400mm	10 Metres
5.0mm	1400mm	10 Metres
6.0mm	1400mm	10 Metres

Thickness	Width	Length
8.0mm	1400mm	10 Metres
10.0mm	1400mm	10 Metres
12.0mm	1400mm	5 Metres
15.0mm	1400mm	5 Metres
20.0mm	1400mm	5 Metres
25.0mm	1400mm	5 Metres

IN EACH CASE CUT LENGTHS, PARTS OR STRIP  
CAN BE SUPPLIED – PLEASE ENQUIRE

WE CAN ALSO OFFER THESE MATERIALS  
WITH A SELF-ADHESIVE BACKING