FISCHBEIN-SAXON

SMART SOLUTIONS™
TO CLOSE «OPEN MOUTH» BAGS



Saxon SB 1000 Band Sealer

- Wider seals possible
- Easy maintenance

The Saxon SB 1000 Band Sealer uses the principle of transfer by conduction where fixed heating elements heat the bags by direct contact through a pair of Teflon coated fibreglass bands. These bands have high thermal conductivity and move in synchronisation with transport belts.

The new SB 1000 features a high efficiency band-sealing module and enhanced cooling capabilities that ensures perfect seals on bags or pouches made from polyethylene, polylaminates, co-extrusion and shrink films.

Fischbein-Saxon SB 1000 produces reliable, aesthetic bag seals up to 12 mm wide. Plus, user-friendly controls that include a variable speed drive (VFD) and an electric variable height pedestal let the operator make fast, efficient product changeovers. The unit's open modular design simplifies maintenance and reduces downtime.

Key features:

. Self aligning heating bars:

-Reduced set up

- Easy and fast change of bands:
 - -Easy maintenance
- Larger seals: -Appearance of the seal
- New mainframe: simplified design:
 - -No food trap
 - No debris
 - -Hygienic
- Stainless steel:
 - -Washable without risk of rust
 - -Ideal for food products
- VFD speed controller (standard):
 - Easy operation
 - -Low cost (no pulley to change)
 - -Easy change over
- Electric column:
 - -Modern
 - -Easy to install
 - -Easy adjustments

The new SB 1000 is part of the company's continuing commitment to provide the industry with technologically advanced band sealers for closing all types of plastic bags/pouches in all kinds of environments. It is

a smart solution for your bagging needs.


Options available: left to right operating direction, horizontal position, extended bottom plate (infeed), bag top trimmer, coders (imprint & embossed), airwash (to clean the "mouth" of the bag immediately prior to sealing), Atex versions, pressurized cabinet (air purge), bag top cooler, extra PIDs, medical version, extension arm, various voltages, wash-down version

www.fischbein.com

Reliable, low-maintenance direct-drive gearbox uses food-grade lubricant



Simplified archit downtimes and an easier mainte



FISCHBEIN-SAXON

Dimensions (head only)

Height 318mm 1017mm Width 651mm Depth 45 ka Weight

Mobile trolley...... 900X910X110mm (height) 850 to 1350mm Column (floor to sealing line)

920 to 1425mm

(floor to sealing line with extension arm)

Electrical

220-240VAC Power supply 889W Power Maximum current..... 3.9A

Pneumatic

No need. Air could be needed for some optional extras.

Closing Speed

Standard speed: 6,2m/min up to 14,1m/min Optional speeds: 2,7m/min up to 6,2m/min

9,7m/min up to 22,2m/min

8 434 - 510 IMPORTANT Levelling Feet must be used if this dimension exceeds 460 Leveling Feet

World Headquarters

USA:

Fischbein Company 151 Walker Road Statesville, NC 28625 • USA

Tel: +1 704 871 11 59 Fax: +1 704 872 33 03 E-mail: sales@fischbein.com

FRANCE:

Corporate Office Fischbein France S.A.R.L. 2, Rue de la Fontaine du Vaisseau/BP 100 F-94123 Fontenay-sous-Bois / Cedex

Tel: +33 1 48 77 15 34 Fax: +33 1 48 77 26 41 E-mail: info@fischbein.fr

SINGAPORE:

Corporate Office Fischbein Packaging (Singapore) PTE, LTD. n°37, Lorong 23, Geylang 02-03 Yu Li Industrial Building Singapore 388371 Tel: +65 67 45 0161/0246 Fax: +65 67 45 1478 E-mail: fipacadm@mbox2.singnet.com

Headquarters Eastern Hemisphere:

BELGIUM: Fischbein S.A. Paepsem Business Park **Boulevard Paepsem 18b** B-1070 Brussels . Belgium Tel: +32 2 555 11 70 Fax: +32 2 520 33 90

E-mail: sales@fischbein.be

GREAT BRITAIN:

Corporate Office Fischbein-Saxon, Ltd Alexandra Business Centre 274 Alma Road Enfield, Middlesex, EN3 7RS • UK Tel: +44 870 1609314 Fax: +44 870 1609315 E-mail: sales@fischbein-saxon.co.uk

GERMANY:

Liaison Office Meisen Straße 96 D-33607 Bielefeld . Germany Tel: +49 521 2997 212 Fax +49 521 2997 213 E-mail: info@fischbein-online.de

www.fischbein.com

Distributed by:

A.T. Sack Fillers Ltd

12 Biggin Lane Ramsey

Cambridgeshire. PE26 1NB. UK.

Tel. 01487 711114

F-mail. info@atsackfillers.co.uk Web. www.atsackfillers.co.uk