

Size (in)	OD (mm)	sch 5 wt	kg/mtr	sch10s wt	kg/mtr	sch10 wt	kg/mtr	Sch40s wt	kg/mtr	Sch 40	kg/mtr
½"	21.33	1.65	0.5	2.11	0.6			2.77	0.7	2.77	0.7
¾"	26.7	1.65	0.6	2.11	0.8			2.87	1.0	2.87	1.0
1"	33.4	1.65	0.8	2.77	1.2			3.38	1.4	3.38	1.4
1½"	48.3	1.65	1.1	2.77	1.8			3.68	2.3	3.68	2.3
2"	60.3	1.65	1.4	2.77	2.3			3.91	3.1	3.91	3.1
2½"	73	2.11	2.2	3.05	3.1			5.16	4.9	5.16	4.9
3"	88.9	2.11	2.6	3.05	3.8			5.49	6.4	5.49	6.4
4"	114.3	2.11	3.4	3.05	4.9			6.02	9.2	6.02	9.2
5"	141.3	2.77	5.5	3.4	6.7			6.55	12.4	6.55	12.4
6"	168.3	2.77	6.5	3.4	7.9	3.4	7.9	7.11	16.1	7.11	16.1
8"	219.1	2.77	8.4	3.76	11.6	3.76	11.6	8.18	24.3	8.18	24.3
10"	273.1	3.4	12.9	4.19	16.2	4.19	16.2	9.27	34.4	9.27	34.4
12"	323.9	3.96	17.8	4.57	20.9	4.57	20.9	9.53	42.1	10.31	45.5
14"	355.6	3.96	19.6	4.78	24	6.35	31.2	9.53	46.4	11.13	53.9
16"	406.4	4.19	23.7	4.78	27.5	6.35	35.7	9.53	53.2	12.7	70.3
18"	457.2	4.19	26.7	4.78	31.0	6.35	40.2	9.53	59.9	14.27	88.8
20"	508	4.78	33.8	5.54	39.9	6.35	44.7	9.53	66.8	15.09	104.6
22"	558.8	4.78	37.2	5.54	43.9	6.35	49.3	9.53	73.6		
24"	610	5.54	47	6.35	54.9	6.35	53.9	9.53	80.4	17.48	145.6

Pipe specification ASTM B861/862 Grade 2