PA EQUIPMENT Technical specification

30W RMS Mixer amplifier

Adastra



Mixer amplifier giving 30W rms output power featuring 2 mic inputs and 1 line input. Switchable VOX priority and balanced XLR input on MIC channel 1. Technical specification

		230Vac, 50Hz 2Vdc (5A)	
		40W	
Г.H.D		30W	
		30W	
		100Hz - 12kHz (±3dB)	
		1.8k ohms	
Input impedance:Aux/Line			
Input sensitivity:Mic 1 (balanced)		1.5mV (-56.4dBV)	
Input sensitivity:Mic 2 (unbalanced)		1.5mV (-56.4dBV)	
anced)		300mV (-10.4dBV)	
		8 ohms & 100V	
		1V @ 600 ohms	
		425 x 88 x 230mm	
		5kg	
Order code	Pric	e each	
700-150	£95	.00	
	nced) alanced) anced) Order code	nced) alanced) anced) Order Pric code	

Power:Mains		230Vac, 50Hz
Power:Battery		12Vdc (8A)
Output power:Max.		70W
Output power: RMS < 2%	T.H.D	60W
DC power		42W
Frequency response		100Hz - 12kHz (±3dB)
Input impedance:Mic		1.8k ohms
Input impedance:Aux/Line		10k ohms
Input sensitivity:Mic 1 (bala	1.5mV (-56.4dBV)	
Input sensitivity:Mic 2 (unbalanced)		1.5mV (-56.4dBV)
Input sensitivity:Mic 3 (unbalanced)		1.5mV (-56.4dBV)
Input sensitivity:Line (unbalanced)		300mV (-10.4dBV)
Input sensitivity:Aux (unba	lanced)	300mV (-10.4dBV)
Outputs:Speaker		8 ohms & 100V
Output:Line		1V @ 600 ohms
Dimensions		425 x 88 x 230mm
Weight		7.5kg
Туре	Order	Price each
	code	
60W mixer/amp Black	700-152	£122.00

For the full range of PA and Disco equipment visit our website at www.electronelec.co.uk

60W RMS Mixer amplifier

Mixer amplifier giving 60W rms of output power featuring 3 mic inputs and 1 line input. Switchable VOX priority and balanced XLR input on MIC channel 1. Channel 3 switchable MIC/AUX.

ELECTRON ELECTRONICS TELEPHONE 01737 841568 FAX 01737 841608 MOBILE 07860 632 869 EMAIL sales@electronelec.co.uk WEB www.electronelec.co.uk

Adastra

120W RMS Mixer amplifier

Technical specification

Adastra

Technical specification



Mixer amplifier giving 120W rms of output power featuring 3 mic inputs and 1 line input. Switchable VOX priority and balanced XLR input on MIC channel 1. Channel 3 switchable MIC/AUX.

Power:Mains	230Vac	, 50Hz
Power:Battery	24Vdc (8A)
Output power:Max.	160W	
Output power: RMS < 2% T.H.D	120W	
DC power	92W	
Frequency response	100Hz -	12kHz (±3dB)
Input impedance:Mic	1.8k ohr	ms
Input sensitivity:Mic 1 (balanced)	1.5mV (-56.4dBV)
Input sensitivity:Mic 2 (unbalanced)	1.5mV (-56.4dBV)
Input sensitivity:Mic 3 (unbalanced)	1.5mV (-56.4dBV)	
Input sensitivity:Line (unbalanced)	300mV (-10.4dBV)	
Input sensitivity:Aux (unbalanced)	300mV (-10.4dBV)	
Signal to noise ratio:Line	>75dB	
Signal to noise ratio:Mic	>70dB	
Outputs:Speaker	8 ohms	& 100V
Output:Line	1V @ 600 ohms	
Dimensions	425 x 88	8 x 230mm
Weight	10kg	
Туре	Order	Price each
	code	
120W mixer/amp Black	700-154	£139.00

120W RMS Slave amplifier

A 120W rms high power slave amplifier for use with the 900 series mixer amplifiers or with any other suitable source. Featuring phono sockets for input and output signals and front located master volume control. Signal and peak LED indicators for visual reading of the amplifiers performance.

Adastra

Power supply		230Vac, 50Hz
Power:Battery		24Vdc (8A)
Output power:Max.		160W
Output power: RMS < 2% T.H.D		120W
DC power		92W
Frequency response		100Hz - 12kHz (±3dB)
Signal to noise ratio		>75dB
Input sensitivity:Line (unbalanced)		300mV
Outputs:Speaker		8 ohms & 100V
Output:Line	1V @ 600 ohms	
Dimensions	425 x 88 x 230mm	
Weight		9.5kg
Туре	Order	Price each
	code	
120W slave amp Black	700-156	£119.00

240W RMS Slave amplifier



A 240W rms high power slave amplifier for use with the 900 series mixer amplifiers or with any other suitable source. Featuring phono sockets for input and output signals and front located master volume

Adastra

Technical specification		
Power:Mains		230Vac, 50Hz
Power:Battery		24Vdc (16A)
Output power:Max.		320W
Output power: RMS < 2% T.H.D		240W
DC power		170W
Frequency response		100Hz - 12kHz (±3dB)
Signal to noise ratio:Line		>75dB
Signal to noise ratio:Mic		>70dB
Input sensitivity:Line (unbalanced)		300mV
Dimensions		425 x 88 x 230mm
Weight		12.0kg
Туре	Order	Price each
	code	
240W slave amp Black	700-158	£189.00

ELECTRON ELECTRONICS TELEPHONE 01737 841568 MOBILE 07860 632 869 EMAIL sales@electronelec.co.uk WEB www.electronelec.co.uk

FAX 01737 841608

Citronic

4 mic/instrument/line

8 Channel mixer



and two stereo inputs

12 Channel Mixer with DSP

A professional mixing console which accepts microphone, electric guitar, keyboard and tape making it ideal for live PA, permanent installation or home recording applications. The unit offers a wide range of features and functions.

code

700-171

£269.00

Citronic

	Microphone (XLR) or line (6.3mm) jac inputs with inserts	k	
Variable input trim (+3 to +50dB for microphones and -22 to +25dB for	2 channels with stereo left and right (RCA) phono inputs		and an and an
line level input)	· /· ·		
4 mic/Instrument/line & 2 stereo line inputs	Tape in, record out		
XLR microphone input	Main stereo output via (XLR) and contr	rol room outpu	ut via (6.3mm) jack
6.3mm instrument/line input	Dual 16 program effects processors wi effect)	th 16 parame	ters (4 memories for each
Level, pan, pre/post fade aux send, 2 -band EQ controls on each channel	3 band EQ on each channel, with mid	frequency cor	ntrol
RCA tape IN/OUT	9 band graphic equalizer on the maste	r section	
Phantom power +48V	+48V phantom power		
Effects send and return	Headphone output		
Headphone output with level control	2 footswitch inputs for the dual effects		
AC/AC adaptor supplied	2 aux/send returns		
Specification:	Standby channel mute		
Power supply 2 x 17Vac @ 590mA	Feedback channel locating (FCL) syste	em and pre-fa	de listen (PFL) for each
Equalizer : High ±15dB @ 12kHz	12-bar LED monitor display		
Equalizer : Low ±15dB @ 80Hz	Mains adaptor supplied		
Frequency response 20Hz - 20kHz	Specification:		
Input impedance : CD/tape IN 24k Ohms	Power supply 16Vac		
Input impedance : Mic 2.3k Ohms			
Input impedance : Stereo line 1M Ohms	Equalizer ±15dB		
S/N ratio -102dBu	Frequency response 20Hz - 20kHz		
THD <0.025%@ +4 dBu output	Headphone output 300mW @ 32 ohm		
Dimensions 263 x 67 x 270mm	Signal to noise ratio >82dB		
Weight 2.4kg	THD <0.01%		
	Туре	Order	Price each

12 channel mixer

Туре	Order	Price each
	code	
8 channel mixer	700-170	£149.00

PA EQUIPMENT Citronic **Disco / PA speakers**

12 Channel Microphone Mixer/Amp



12-channel powered live mixer

On-board 24-bit digital effects processor with LCD screen

A superb 12-channel powered live mixer, keenly priced with performance, specification and facilities that are exceptional value for money. Whether your application is for live PA, permanent installation or home recording you'll be pleasantly surprised with the quality reproduction at such a low cost. Citronic CLP122DSP



A range of high power trapezoidal speaker boxes giving excellent sound reproduction. They all contain a high power bass woofer with a large magnet and a high compression piezo horn for the mid and high frequencies. Fitted with small pitch metal grill, carrying handles and top hats. Gold plated 4mm terminals and a 6.35mm jack socket Top hat. Impedance 8R

12-channels with microphone (XLR) or Line (1/4") jack inputs	Technical specificat	ion		
Effect send and return	Frequency response	70Hz - 17kHz (8")		
Headphone input with PFL on each channel		60Hz - 18kHz (10")		
		50Hz - 20kHz (12")		
3-band EQ per channel		40Hz - 20kHz (15")		
Dual 7-band master EQ	Dimensions	305 x 280 x 490mm (8")		
48V phantom power		400 x 330 x 550mm (10")		
Supplied with gooseneck lamp		400 x 380 x 620mm (12")		
		480 x 430 X 690mm (15")		
Specification:				
Power supply 230Vac, 50Hz	Weight	9.0Kg (8")		
Crosstalk <-60dB		11.0Kg (10")		
		15.5Kg (12")		
Equalizer : Bass 120Hz ±15dB		20.0Kg (15")		
Equalizer : Midrange 350Hz - 8kHz ±15dB				
Equalizer : Treble 12kHz ±15dB	Туре		Order	Price ea
Frequency response 20Hz - 20kHz			code	
Output power : 4 Ohms 2 x 400W	8" 150W bass reflex	speaker	700-190	£33.00
	10" 200W bass refle	ex speaker	700-191	£42.00
Output power : 8 Ohms 2 x 250W	12" 250W bass refle	ex speaker	700-192	£59.00
Signal to noise ratio >100dB	15" 300W bass refle	ex speaker	700-193	£84.00
THD <0.02%				

For the full range of PA and Disco equipment visit our website at www.electronelec.co.uk

Туре	Order	Price each
	code	
12 channel mixer/Amplifier	700-172	£390.00

Dimensions 410 x 513 x 185mm(9U)

ELECTRON ELECTRONICS TELEPHONE 01737 841568 FAX 01737 841608 MOBILE 07860 632 869 EMAIL sales@electronelec.co.uk WEB www.electronelec.co.uk

Skytec

Price each

Column speakers



Technical specification



Two modern slimline column speakers ideally suited for all indoor applications especially where discretion is a necessity. They are also suitable for outside use provided they are sited under cover. Extruded aluminium with a white protective finish and fitted with a white metal grill and white plastic end caps. Fitted with high quality 21/2" round speakers providing a crisp clear sound reproduction and a 100V line matching transformer and a length of connecting cable. Wattage tappings are selected by an integral rotary switch. Supplied with mounting brackets

700-197

700-198 700-199 Power rms 15W 10W 15W Power max. 23W Tappings 0.7,55, 2.5, 1.25W Impedance 8R 1K, 1.67K, 2K, 4K, 8K Frequency response 275Hz - 7kHz 300Hz - 13kHz SPL@ 1kHz 1W/1m 106dB 105dB SPL@ 1kHz rated 1m 118dB 115dB Dimensions 240 x 205mm dia 252 x 185mm dia Weight 1.42kg 1.5kg 700-200 700-201 Power rms 15W 25W Power max. 23W 38W Tappings 15, 10, 5, 2.5W 25, 20, 15, 10, 5W Impedance 400, 500, 670, 1K, 2K 670. 1K. 2K. 4K 275Hz - 7kHz 250Hz - 10kHz Frequency response SPL@ 1kHz 1W/1m 106dB 108dB SPL@ 1kHz rated 1m 118dB 115dB Dimensions 273 x 205mm dia 310x 270mm dia 1.78kg Weight 2.34ka Order Price each Type code 15W 8R horn speaker 700-198 £22.00 15W 100v horn speaker 700-199 £31 00 25W 100v horn speaker £39.90 700-200 30W 100v horn speaker 700-200 £39.90

Free delivery in the UK on all orders over £30

Technical specification 700-196

Speakers	4		7	
Power rms	12W		20W	
Power max.	24W		40W	
Tappings	1.5/3/6/12W		2.5/5/1	0/20W
Impedance	833/1.66/3.3/6.6	К	500/1K	/2K/4K
Frequency response	250Hz - 16kHz		250Hz	- 16kHz
SPL@1W/1m	94dB		94dB	
Dimensions	406 x 105 X 75n	nm	620 x 1	05 x 75mm
Weight	2.2kg		3.6kg	
Туре		Orde	r	Price each
		code		
12W column speaker	r	700-	196	£37.00
20W column speaker	r	700-	197	£54.00

Horn speakers

Adastra

A long established range of heavy duty, high quality circular PA horn speakers. Made from virtually indestructible ABS material offering maximum protection against shock and weather making them ideal for mounting in extreme outdoor conditions; IP rating 65. All horns are fitted with a sturdy, 270° adjustable mounting bracket and a 60cm length of double insulated connecting cable. All models are fitted with high quality aluminium voice coils which offer high acoustical properties and reliability. 100V line models have high quality line matching transformers fitted into a sealed rear housing with wattage tappings selectable by an integral rotary switch.

ELECTRON ELECTRONICS TELEPHONE 01737 841568FAX 01737 841608MOBILE 07860 632 869EMAIL sales@electronelec.co.ukWEB www.electronelec.co.uk

Dynamic Microphone



Dynamic, unidirectional

Skytronic

A Dynamic handheld microphone with contemporary styling, producing a well-rounded sound with good warm bass response, and smooth high frequency reproduction. The microphone's cardioid pick-up capsule is mounted on a rubber suspension to minimize handling noise. On/Off switch and 6m lead with XLR connector.

Condenser Microphone



Aluminium body condenser microphone with "back electret" transducer system ensuring a smooth frequency response. Powered by a 1.5V battery making it suitable to be used over long distances without the need for a phantom power supply. The cardioid pattern eliminates feed back.

Skytronic

Frequency response			60Hz - 15kHz
Impedance			600 Ohms
Sensitivity			-75dB
Microphone:Connector			XLR
Connector			6.3mm mono
Lead length			6m
Dimensions			178 x 53mmØ
Weight			290g
Туре	Order	Price	each
	code		
Dynamic mic 600R	700-320	£6.25	5

Frequency response			100Hz - 16kHz
Impedance			600 ohms
Sensitivity			-68dB
Battery			1.5V (1 x AA)
Microphone:Connector			XLR
Connector			6.3mm mono
Lead length			5m
Dimensions			185 x 26mmØ
Weight			575g
Туре	Order	Price eac	h
	code		
Condenser microphone	700-322	£24.90	

Hand held Radio microphones



Mains adaptor supplied

Power supply	12Vdc, 300mA
THD	< 1%
Sensitivity	10µV @ 60dB S/N
Signal to noise ratio	87dB
Audio output	350mV
Image rejection	>50dB
Battery	9V (1 x PP3)
Battery life (hours)	15 - 20
RF output power	2mW
Dynamic range	>=90dB

Super unidirectional

Frequency response

Skytronic

A dynamic microphone with unidirectional pattern. Due to its special construction and optimal front-rear ratio, it is ideal for singers. The strong metal body with shockproof cartridge and built-in noise suppressor also has an On/Off switch.

40Hz - 18kHz

ELECTRON ELECTRONICS TELEPHONE 01737 841568 MOBILE 07860 632 869 EMAIL sales@electronelec.co.uk WEB www.electronelec.co.uk

FAX 01737 841608

Audio Technica

lower price

The handheld microphone system offers excellent sound quality, easy operation, long term dependability and is recommended for the vocal artist, Karaoke and DJs. A professional VHF wireless system designed primarily for use in vocal entertainment, speech and sound reinforcement applications. Includes a non-diversity, single channel, dual antenna receiver and a handheld transmitter on a specific crystal controlled frequency.

300 ohms Impedance Sensitivity -74dB XLR Microphone:Connector Connector 6.3mm mond Lead length 5m Dimensions 170 x 50mmØ Weight 3650 Туре Order Price each code Dynamic microphone 700-321 £15.90

Skytronic

Consumption	30mA			
Dimensions:Microphone	241 x 53n	241 x 53mmØ		
Dimensions:Receiver	110 x 35 :	110 x 35 x 210mm		
Weight:Microphone	360g			
Weight:Receiver	289g			
Туре	Order	Price each		
Handheld radio mic 173.8mHz	code 700-311	£89.00		
Handheld radio mic 174.6mHz	700-310	£89.00		
Handheld radio mic 175mHz	700-312	£89.00		

Tie clip Radio microphones

Audio Technica

Mains adaptor supplied

Signal to noise ratio

Power supply

THD

Sensitivity

Audio output

Battery

Image rejection

Battery life (hours)

RF output power

Dynamic range

Consumption

Dimensions:Microphone

Tie-clip radio mic 173.8

Dimensions:Receiver

Weight:Microphone

Weight:Receiver

Туре

This system has a small lapel microphone for hands free use in church theatre, conferences or presentations. The microphone is easily attached to clothing using the clip provided and an open pore foam windshield effectively reduces wind noise ("popping") . A professional VHF wireless system designed primarily for use in vocal entertainment, speech and sound reinforcement applications. Includes a non-diversity, single channel, dual antenna receiver and a body-pack transmitter on a specific crystal controlled frequency.

12Vdc, 300mA

10µV @ 60dB

< 1%

87dB

350mV

>50dB

15 - 20

2mW

>=90dB

30mA

78g

2890

£89.00

£89.00

£89.00

Order code

700-313

Price each

265 x 110 x 25.4mm

110 x 35 x 210mm

9V (1 x PP3)

lower price

Type Order Price each 1-2 code 700-342 £12.95 Microphone stand black

Dynamic mic windshields



Туре

A pack of 5 black foam windshields to fit most sizes of dynamic microphones

Microphone wind shield black pk 5 700-350 £1.85

Condenser mic windshields

Skytronic



A windshield suitable for most 5mm dia condenser microphones

Туре	Order	Price each	
	code		
Condenser wind shield black	700-351	£0.22	

Tie-clip radiomic 174.6 700-314 Tie-clip radio mic 175 700-315 ELECTRON ELECTRONICS TELEPHONE 01737 841568

MOBILE 07860 632 869

FAX 01737 841608

EMAIL sales@electronelec.co.uk WEB www.electronelec.co.uk

Budget Microphone stand

Budget microphone stand with boom arm and sturdy base. Height adjustable between 0.95m and 1.60m. Supplied with microphone holder adaptor.

0.95 - 1.5m Height 750 x 640mm Boom arm Weight 2.6kg

A professional quality, very stable,

Available in chrome or black with black

accessories. Height adjustable from 0.95m

0.9 - 1.5m

3kg

3+

£10.95

£10.95

750 x 640mm

microphone stand with boom arm.

Price each Туре Order 1-2 3+ code 700-340 £13 50 £11.90 Budget Mic stand black £11.90 Budget Mic stand chrome 700-343 £13.50

to 1.6m.

Height

Weight

Boom arm

Microphone stand

Microphone stand chrome 700-341 £12.95

Skytronic

Skytronic

Order

code

Price each

72 PA EQUIPMENT								
Smoke machine		Soundlab	5 litre smoke fluid		Soundlab			
A discrete smoke generator for co cealed use. Made from metal and ished in black with a wired remo- control. Colour Blue Dimensions 112x115x226mm Weight 2.85kg	fin-							
Power Input 230Vac@50Hz Control Style Hand remote Fluid Capacity 0.51		•	Туре	Order code	Price each			
Heatup Time 4 mins			Smoke fluid 5 litre	725-005	£12.90			
Туре	Order code	Price each	5 litre heavy duty fog		Soundlab			
Smoke machine	725-001	£23.00		27				
Smoke machine 700W		Soundlab						
A reliable and effective smoke genera Features 1 litre capacity built in ta wired remote control. Made from t tinted transparent plastic.	ank,		Туре	Order code	Price each			
Colour Blue Dimensions 145x160x315mm			Heavy duty extra fog 5 litre	725-004	£18.50			
Weight 4.5kg Power Input 230Vac@50Hz Packing Box		Sound LAB	Mini snow machine		Soundlab			
Control Style Hand remote Fluid Capacity 1I Heatup Time 5 mins			Compact snow machine. Product fea tures 1 litre tank, high output, projects snow up to 6m, remote control, uses Soundlab snow fluid.	5				
Heater Size 700W Type	Order code	Price each	Colour Black Dimensions 138x176x323mm Weight 3.6Kg Power Input 230Vac@50Hz					
Smoke machine 700W	725-002	£32.00	Fluid Capacity 1I					
			Туре	Order	Price each			
DJ smoke fluid		Soundlab		code				
Water based liquid designed for use u	vith		Mini snow machine	725-010	£39.90			
Water based liquid designed for use v most common brands of smoke machi This product is designed to give low p sistence and density and is suitable	ne. er-	Ô	1 litre snow and foam fluid 5 litre snow and foam fluid	725-011 725-012	£4.90 £9.90			
Туре	Order	Price each						
	code							
1 Ltr DJ smoke fluid	725-003	£3.90						

ELECTRON ELECTRONICSTELEPHONE 01737 841568FAX 01737 841608MOBILE 07860 632 869EMAIL sales@electronelec.co.ukWEB www.electronelec.co.uk