108

SPEAKERS

Miniature round loudspeaker



A minature loudspeaker ideal for small projects.Handling capacity 300mW.Frequency response 300-5000 Hz.Diameter 2.5 inch.

Туре	Order	Price each		
	code	1-24	25-99	100+
64R 2.5" loudspeaker	580-310	£0.59	£0.52	£0.45
8R 2.5" loudspeaker	580-316	£0.55	£0.47	£0.39

10W 75MM loudspeaker

Full range speaker. Foam edged paper cone with chrome HF



new

Colour Black Dimensions 40x78x78mm

Weight 0.4 kg

Resonant Frequency 120hZ

Magnet Weight 0.15KG

Impedance 80hm

Sensitivity 88dB

Peak Music Power 20W

Power RMS 10W

Frequency Response 120-16000Hz

Diameter 78mm

Type	Order	Price eac	h
	code	1-9	10+
75mm 10W loudspeaker	580-313	£3.75	£3.35

12" General purpose Loudspeaker

A general purpose speaker with a frequency range of 35 to 18kHz ideal for voice and music reproduction Housed in a strong steel basket with a paper cone and dual construction tweeter. Heavy magnet and large voice coil making this speaker perfect replacement for most applications. Impedance 8R. Power 100W RMS. Diameter 12". SPL (1W/1m) 91dB



Туре	Order	Price each	
	code	1-4	5+
12" 100W loudspeaker	580-320	£14.90	£13.50

12" Pro music woofer

Constructed from heavy-duty-die-cast aluminium and incorporating a strong 75mm Kapton voice coil with a paper coated cone. Power 250W RMS. Impedance 8R. Frequency range 27-5kHz. SPL (1W/1m) 91dB. Fitted with gold plated push terminals



Туре	Order	Price each	
	code		
12" 250W Woofer	580-321	£31.50	

15" Pro music woofer

Constructed from heavy-duty-die-cast aluminium and incorporating a strong 75mm Kapton voice coil with a paper coated cone. Power 3000W RMS. Impedance 8R. Frequency range 20-4kHz. SPL (1W/1m) 92dB. Fitted with gold plated push terminals



Туре	Order	Price each
	code	
15" 300W Woofer	580-322	£42.90

SPEAKERS

109

6" Sovereign 6-100 Loudspeaker

Fane new

12" Sovereign 12-125 Loudspeaker

Fane new

Medium Power Driver ideal for use in PA systems as well as MI and Pro Sound applications. Works well for midrange in a small sealed box or a mid/bass driver in vented boxes.

Resonant Frequency 111Hz

Magnet Weight 20oz

Impedance 80hm

Coil Size 38.1mm/1.5in

Sensitivity 94.7dB

Power RMS 100W

Type Order Price each

code

Fane Sovereign 6-100 580-450 £21.25

Medium Power Driver ideal for use in PA systems as well as MI and Pro Sound applications. Works well for midrange in a small sealed box or a mid/bass driver in vented boxes. Great for bass guitar in medium sized vented cabinets.

Resonant Frequency 47Hz

Magnet Weight 20oz

Impedance 80hm

Coil Size 38.1mm/1.5in

Sensitivity 96.5dB

Power RMS 125W

Frequency Response 45-8000Hz

Diameter 305mm/12in

Type Order Price each

code

Fane Sovereign 12-125 580-453 £36.99

8" Sovereign 8-125 Loudspeaker

Fane new

12" Sovereign 12-300 Loudspeaker

Fane

new

Medium Power Driver ideal for use in PA systems as well as MI and Pro Sound applications. Works well for midrange in a small sealed box or a mid/bass driver in vented boxes. Great for bass guitar in medium sized vented cabinets.

Resonant Frequency 73.9Hz

Impedance 80hm

Sensitivity 93.7dB

Power RMS 125W

Frequency Response 52Hz-4.7kHz

Diameter 209.3mm

Type Order Price each

code

Fane Sovereign 8-125 580-451 £22.95

Medium Power Driver ideal for use in PA systems as well as MI and Pro Sound applications. Works well for midrange in a small sealed box or a mid/bass driver in vented boxes.

Resonant Frequency 50Hz

Magnet Weight 57oz

Impedance 80hm Sensitivity 100W

Power RMS 300W

Frequency Response 65-4000Hz

Diameter 305mm/12in

Type Order Price each

code

Fane Sovereign 12-300 580-454 £42.25

10" Sovereign 10-125 Loudspeaker

Fane new

Medium Power Driver ideal for use in pa systems as well as MI and Pro Sound applications. Works well for midrange in a small sealed box or a mid/bass driver in vented boxes. Great for bass guitar in medium sized vented

Resonant Frequency 50Hz

Magnet Weight 20oz

Impedance 80hm

Sensitivity 95.3dB Power RMS 125W

Frequency Response 54-5000Hz

Diameter 254mm

Type Order Price each

code

Fane Sovereign 10-125 580-452 £25.45



A larger range of loudspeakers are available online at www.electronelec.co.uk

ELECTRON ELECTRONICS TELEPHONE 01737 841568

FAX 01737 841608

MOBILE 07860 632 869

EMAIL sales@electronelec.co.uk WEB www.electronelec.co.uk

110

SPEAKERS

Type

12" Colossus 12MB Loudspeaker

Fane new Order

Price each

code

Fane Colossus 15B-600

580-456 £159.00

The Colossus 12MB is intended for use as a very high output bass mid driver in a two way ported enclosures and also as a bass driver in multiway systems. The unit features a 3 inch voice coil driven by a non inductive motor system which dramatically reduces third harmonic and intermodulation distortion. The cone membrane, manufactured from Polycellulose, is much stronger and more durable than conventional paper pulp alternatives.



This allows the driver to combine high sensitivity with the structural integrity required to produce undistorted lofrequencies at high output levels. The mechanical and electrical properties of the unit have been carefully optimised to allow extended low frequency output up to it's rated power handling of 450 Watts (A.E.S continuous). Heat is dissipated from the ultra light aluminium voice coil by a composite glass fibre and black anodised aluminium former. This assists in yielding outstanding power handling from a 3 inch coil, with peak power handling in excess of 1800 Watts! The driver exhibits an average sensitivity of 98 dB and is best used in ported enclosures of 25 to 80 litres.

Resonant Frequency 55Hz

Magnet Weight 93oz

Impedance 80hm

Coil Size 77mm/3in

Sensitivity 98dB

Power RMS 450W

Frequency Response 4-3.5kHz

Diameter 305mm/12in

Order Price each Type

code

Fane Colossus 12MB 580-455 £124 50



Piezo Tweeter

A special piezo high impedance tweeter featuring high efficiency without loading the amplifier too much. Can be connected easily via a small series resistance without special filter. Crisp, clean reproduction of the high frequencies.

Frequency response 4kHz - 30kHz

Impedance:25kHz 60 - 80 ohms

Impedance:1kHz 1k ohms

Dimensions: 85x85x70



Туре		Order	Price each		
		code	1-4	5-9	10+
Piezo horn	tweeter 85x85	580-325	£1.40	£1.20	£0.95

Piezo Tweeter

A special piezo high impedance tweeter featuring high efficiency without loading the amplifier too much. Can be connected easily via a small series resistance without special filter. Crisp, clean reproduction of the high frequencies.

Frequency response 4kHz - 30kHz Impedance:25kHz 60 - 80 ohms

Impedance:1kHz 1k ohms Dimensions: 67x145x50



15" Colossus 15B-600 Loudspeaker Fane new

The Colossus 15B-600 is intended for use in high power two way ported enclosures and as a high output bass driver in multiway systems. It features a 4 inch voice coil immersed in a symmetric magnetic field yielding increased linearity and lower distortion at high excursion levels. The cone membrane, manufactured from Polycellulose, is much stronger and more durable than conventional paper pulp



Type Order Price each

This allows the driver to combine high sensitivity with the structural integrity required to produce undistorted low frequencies at high output levels. The driver handles 600 Watts (A.E.S) continuous and can cope with peaks in excess of 2400 Watts. This is due to advanced thermal management in the form of vented diecast chassis and motor system coupled to a large vaned heatsink mounted on the rear of the unit. These measures effectively remove heat from the voice coil resulting in extremely low power compression. The Colossus 15B-600 exhibits

an average sensitivity of 99 dB and can deliver bass down to 40 Hz (-6

Resonant Frequency 42Hz

dB) in a 125 litre ported enclosure.

Magnet Weight 120oz

Impedance 80hm

Coil Size 102mm/4in

Sensitivity 99dB

Power RMS 600W

Frequency Response 40Hz-3kHz

code 1-4 5-9 10+ Piezo horn tweet 67x145 580-326 £1.20 £0.95 £1.40

Transistor oscillator buzzer

Electronic piezo buzzer 85dB Kepo





Minature transistor oscillator buzzer supplied either with 100mm fly leads or PCB mounting.

A 12V electronic piezo buzzer ideal for alarms emitting an ear piercing sound of 3.5kHz at 85 to 90dB. PCB mounting.

12VDC 10mA. Dimensions 10 x 23mm dia



Technical specification

Operating voltage	6v type	4-8V DC	Туре	Order	Price each	1	
	9v tvpe	6-12V DC		code	1-24	25-99	100+
	,,	8-16V DC	12V buzzer 85dB	580-309	£0.57	£0.51	£0.45
	,	* .*. = *					

Current consumption	25mA								
Sound output	75dB at 30cm				Electronic piezo bu	ızzer 90d	lB		Kepo
Frequency	400Hz								
Туре	Order	Price ea	ch		A 12V electronic piezo al				
	code	1-24	25-99	100+	emitting an ear piercing sound of 3.7kHZ at 100dB. Supplied with fly		W 700 S		
6V buzzer 100mm fly	580-301	£0.49	£0.42	£0.37	leads.	,			
9V buzzer 100mm fly	580-300	£0.49	£0.42	£0.37	.37 12V 15mA. Dimensions 25 x 30mm dia RoHS compliant				
12V buzzer 100mm f	ly 580-302	£0.49	£0.42	£0.37	·		No.		
6V buzzer PCB mnt	580-303	£0.49	£0.42	£0.37					
9V buzzer PCB mnt	580-305	£0.49	£0.42	£0.37	Туре	Order	Price eac	h	
						code	1-24	25-99	100+

Miniature piezo transducer

Kepo 12V buzzer 90dB 3.7kHz 580-308 £0.65

1-24 25-99 100+ £0.58 £0.52



Ultrasonic transducers



A minature flange mounting piezo audio transducer with flying leads.Requires an external drive circuit.Resonant frequency 4KHz.Max voltage 30V p-p square wave. KPR-2310

Туре	Order	Price each		
	code	1-24	25-99	100+
4Khz piezo transducer	580-307	£0.36	£0.32	£0.27

An ultrasonic transmitter and receiver for sending and receivingcontinuous or modulated waves in the 40KHz region through air.Ideal for remote control applications. These units are not watertight.

Туре	Order	Price each
	code	
Transmitter	580-314	£1.75
Receiver	580-315	£1.75

Disc transducer

Kepo



A 1Khz disc transducer ideal for use in greetings cards.Can be connected to our melody generator IC. Dia 25mm. Rohs compliant.

Туре	Order	Price each		
	code	1-24	25-99	100+
1Khz disc transducer	580-304	£0.12	£0.10	£0.08