

Mobile Hot Water Washers / Steam Cleaners



APPLICATIONS

- Garages
- Factories
- Vehicle Fleets
- Heavy Plant
- Farms etc.



TAMMER hot water power washers encompass all the lessons learned over 40 years of Power Washer production. They are designed and built for a long continuous working life.

TAMMER washers feature functional controls, no gimmicks or printed circuits. All circuitry is hard wired and well proven.

TAMMER washers have a strong and manoeuvrable zintec steel chassis with a stainless steel hinged cover, withstanding the knocks and corrosion unlike modern plastic and pressed metal machines.

- Fitted with slow running 3 plunger pumps
- Stainless steel 3 gallon water tank with low level cut out ensures pump protection
- Auto stop will switch machine off automatically if left unused for more than 2 mins
- Auto start can be fitted at no extra charge, but we don't recommend it
- High pressure detergent injection system
- Vertical double wound diesel fired burner unit
- Water temperature can be altered from ambient up to 130oC
- 5 gallon internal diesel fuel tank
- 9m h.p.outlet hose, gun with non kink hose swivel and insulated 900mm lance
- Inlet and outlet hoses fitted with quick release couplings

Technical Specification				
Model	Motor	Voltage	Pressure	Flow
1000H	2.2 kw	110 v	1000 psi.	13 lpm.
1500H	2.2 kw	230 v	1450 psi.	13 lpm.
2200H	4.0 kw	415 v	2200 psi.	14 lpm.
3000H	5.5 kw	415 v	3000 psi.	14 lpm.
Dimensions				
Length: 925mm Width: 638 mm Height: 750 mm Weight 110 kg.				

Pump

3 Plunger positive displacement pump, direct coupled to the motor. All wetted parts non-ferrous. Stainless steel valves. Ceramic liner plungers. Brass cylinder head. Oil filled crankcase with splash lubrication. Conventional crankshaft and con rods.