PRODUCT DATA SHEET HPC 16

CI/SfB Vv4
January 2014

NU-GUARD® NRG COLOUR PRIMER / BASECOAT

DESCRIPTION: Nu-Guard NRG Colour Primer / Basecoat is a new generation, unique, coloured

external coating system utilising the most advanced hybrid chemistry available to

produce superior weather protection for masonry walls and bricks.

ADVANTAGES: • Improve Energy Efficiency for Homes

• Super Hydrophobic Water Repellency

• Excellent Stain Resistance

• Resistant to Dirt and Pollution

• Self Cleaning Properties

Resistant to Weathering

• UV Stability - Permanent

• Natural Clean Appearance

• Permeable to Water Vapour

USES: For use on all bare or previously painted external substrates.

COLOUR RANGE: White / Off White

PACK SIZE: Single component product supplied in 5, 10 or 15 Litre Tubs.

COVERAGE RATE: This is dependant on texture and porosity of the substrate.

On average the coverage rate is 10m^2 / litre per coat applied in 2 coats.

DRYING TIME: Dry and re-coatable in 4-6 Hours @ 20°C

PREPARATION: Remove all loose flaking coatings back to a firm edge.

Remove any organic growth this a stiff bristle (not wire) brush and apply a liberal coat

of Hydron SS1 Sterilising Solution.

Ensure surface to be treated are clean, free from contamination and dry.

APPLICATION: Two coats by brush, roller or spray.

EQUIPMENT CARE: All equipment should be cleaned with water immediately after use.

STORAGE: Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE: 12 months (in original sealed container).

HEALTH & SAFETY: Refer to health and safety sheets.





