

NU-GUARD[®] NRG COLOUR TOPCOAT

DESCRIPTION: Nu-Guard NRG Colour Topcoat is the final coat of a new generation, unique, coloured external coating system utilising the most advanced hybrid chemistry available to produce superior weather protection for masonry walls and bricks.

ADVANTAGES:

- Improve Energy Efficiency for Homes
- Super Hydrophobic Water Repellency
- Excellent Stain Resistance
- Resistant to Dirt and Pollution
- Self Cleaning Properties
- Resistant to Weathering
- UV Stability - Permanent
- Natural Clean Appearance
- Permeable to Water Vapour
- Protects Against Penetrating Damp

USES: For use on all bare or previously painted external substrates.

COLOUR RANGE: Any BS4800 or RAL Colour.

PACK SIZE: Single component product supplied in 5, 10 or 15 Litre Tubs.

COVERAGE RATE: This is dependant on texture and porosity of the substrate. On average the coverage rate is 10m²/ litre applied in 1 coat.

DRYING TIME: Dry in 4-6 Hours @ 20°C

PREPARATION: Apply when the Basecoat is sufficiently dry.

APPLICATION: One coat by brush, roller or spray.

EQUIPMENT CARE: All equipment should be cleaned with water immediately after use.

STORAGE: Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE: 12 months (in original sealed container).

HEALTH & SAFETY: Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494