



THINGS YOU SHOULD KNOW ABOUT THE DEPRAT 89 Tube

Efficient

- Can carry 150kg at 3m wide with only 10mm tube deflection.
- Can carry 50kg at 4.5m wide, ideal for 77mm lath garage doors.
- Tube available in 6m or 7m lengths and can be bought individually.
- Fully galvanised, high corrosion resistance even in coastal regions.
- No degreasing of tubes or painting required and waiting to dry.

Equipment

- Sprung barrels can have several springs, width is only restriction.
- 12 different standard spring sizes available all RH wound.
- Special lifting and locking systems for extruded, foam filled and 3» steel laths.
- Telescopic dummy ends for either normal or 18mm brake options.
- Motors and adaptors available from all leading motor manufacturers.

Simple to use

- After cutting the tube only an allen key and screwdriver are required.
- No drilling or welding of studs for curtain attachments to the tubes
- No welding of dummy ends, push fit into keyed tube and one rivet needed.
- Skilled welders not required for assembly/fabrication.

Time saving

- Huge saving in time and cost of labour for assembly of all types of barrels.
- Minimum of 90 motorised barrels can be assembled by one man in 8 hours.
- It takes only 10 minutes to cut and assemble a spring barrel to completion.

Competitive

Spring barrel assembly

	4"16g Shutter barrel	89 Deprat tube
average time taken	60 min	10 min

6 TIMES
FASTER

Motorised barrel assembly

	4"16g Shutter barrel	89 Deprat tube
average time taken	27 min	5 min

6 TIMES
FASTER

**MORE COST EFFECTIVE THAN ANY OTHER STEEL ROLLER
ON THE MARKET, AND GALVANISED TOO.**