


Grade 8 Master Links



- Meets the performance requirements of BS-EN 1677-4.
- Suitable for use with Grade 8 Chains and wire/fibre rope slings.
- Painted finish.
- Alloy steel, quenched and tempered.
- Designed for use with 1 or 2 leg slings.
- Welded
- Proof load 2.5 times the W.L.L.
- Minimum break load 4 times the W.L.L.
- S/T ranges have large inside widths & lengths to allow for sling hardware and crane hooks.



code	W.L.L. (tonnes)	part no.	D (mm)	P (mm)	L (mm)	weight (kgs/each)
K0701	2.75	S/T-87-8	15	120	70	0.5
K0710	3.55	S/T-108-8	16	140	80	0.67
K0702	5.50	S/T-1310-8	20	160	95	1.21
K0706	9.45	S/T-1613-8	27	190	110	2.65
K0705	14.20	S/T-2016-8	33	230	130	4.78
K0707	22.3	T-2220-8	38	275	150	7.50
K0715	33.4	T-2622-8	45	340	180	12.82
K0717	40.8	T-3226-8	50	350	190	16.50
K0704	2.12	W-87-8	16	110	60	0.53
K0709	3.15	W-108-8	19	135	75	0.92
K0708	5.30	W-1310-8	23	160	90	1.6
K0703	8.00	W-1613-8	27	180	100	2.5
K0712	11.20	W-1816-8	33	200	110	4.2
K0713	17.00	W-2220-8	40	300	160	8.96

NEVER EXCEED MAXIMUM CAPACITY

Ensure operator follows safe use instruction guidelines