

Material Transfer Pumping Equipment

Transfer pumps for low to high viscosity materials



5 Gallon ram mounted pumps with a See-Flo 494 dispense system

Features

- Pneumatic operation
- Pump on demand
- Ball check for low viscosity
- Chop-check for high viscosity
- Divorced design
- Carbon or stainless steel wetted components
- All controls included
- Material 'wet cups' to isolate material from atmosphere
- Various packing configurations












Transfer Pumps





Bung mounted







•Mountings

- •5 rams, single or double post
- •55 gallon, 3.5" or 6.5" double post ram
- •5 or 55 gallon lifts; for low viscosity materials
- •Follower plate seal with single or double seal
- •Bung hole mounted
- •Floor mounting
- •300 gallon magnadrum pump assemblies

Ratio

- •Power ratio's from 1:1 to 64:1
- •Higher ratio for higher viscosity materials

Pump Styles

- •Chop check style for high viscosity materials
- •Ball check style for low viscosity materials

Options

- •Carbon or stainless steel wetted components
- •Teflon coated follower plates
- •Follower seals with different construction for material compatibility
- •Pump low level alert & shut-off
- •Automatic Material Pump Crossover Package for dual pumps
- •55 gallon drum covers with or without agitator



Diaphragm pumps



Form 00-0000 • Copyright 2001



45677 Helm Street • P.O. Box 701460

Plymouth, MI 48170 • USA Phone: (734) 459-8600 Fax: (734) 459-8686

Web: SealantEquipment.com

Email: Sales@SealantEquipment.com