

DIRECT NUMBERS

Orders: 01469 535 301 Estimating: 01469 530 577 01469 535 308

Technical: 01469 535 311 Marketing: 01469 530 577

For all enquiries
please contact the
Howarth Windows & Doors
Sales Office on:
01469 535301

CONTACT DETAILS

Address: The Dock, New Holland, North Lincolnshire DN19 7RT

Telephone: 01469 530 577 Fax: 01469 531 559

Email: windows&doors@howarth-timber.co.uk

Website: www.howarth-timber.co.uk

2013 RANGE

HOWARTH TIMBER WINDOWS & DOORS

FOR SUPERIOR QUALITY,
PERFORMANCE AND FLEXIBILITY
THE SUSTAINABLE TIMBER OPTION





FOR QUALITY AND DURABILITY, HIGH PERFORMANCE DOOR SETS

Improved construction, security and range of styles.

We have improved our extensive range of door sets with the introduction of a revolutionary range of laminated Redwood Nordic Pine panel and French Casement doors.

- Quality laminated softwood construction.
- High security Secured by Design multi-point locking now fitted as standard on all door sets.
- Available with various design, size and colour options.
- Manufactured from the finest PEFC accredited timber on request.
- Extended guarantees for long-lasting peace of mind.




Modern engineered timber windows and doors combining the traditions of sustainable wood with all the higher specification demands of the twenty-first century.


- BFRC A Rated.
- Quality laminated softwood construction.
- Improved thermal performance.
- NEW upgraded efficient
 24mm STORVIK SKD
 Double Glazed unit
 with Ultra Low U-Values
 to 1.2 W/m²K.
- NEW upgraded efficient
 44mm STORVIK SKT

 Triple Glazed unit with
 Ultra Low U-Values to
 0.8 W/m²K.

 NEW - The high security Secured by Design locking system now available as an option on all our windows except the Storvik range where it's fitted as standard.







 Developed, researched, designed and manufactured in the UK by Howarth Timber Windows & Doors specifically for this market.









SLIM PROFILE ULTRA LOW U-VALUE STORVIK DOUBLE AND TRIPLE GLAZED **RANGE**

Meeting and beating the challenges of higher standards.

Designed and manufactured in the UK by Howarth specifically for this market. The upgraded STÓRVIK range was developed after extensive research into the latest in timber, glazing and weather seal products to produce a window design that has driven beyond current standards to those that will be expected of windows in the future.



Quality laminated Redwood Nordic Pine construction.

Supplied fully finished in our extended range of paints and stains.

Secured by Design locking system now available as an option.

Available in various design and size options.

Manufactured from FSC® accredited timber on request.

Extensive guarantees for long-lasting peace of mind.

Modern mechanism allows for easy cleaning and maintenance.

BFRC A to C Rated.

Low U-Values to 1.38 W/m²K.

BRE Green Guide A+ Rated

Incorporating Swisspacer V, the leading warm edge spacer fitted SWISSPACER

A COMPREHENSIVE RANGE OF TIMBER WINDOWS MEETING THE MOST EXACTING SPECIFICATIONS



- Improved thermal performance.
- BFRC A Rated.
- Efficient 24mm STORVIK^{SKD} Double Glazed unit with Ultra Low U-Values to 1.2 W/m²K.
- Efficient 44mm STORVIK^{SKT} Triple Glazed unit with Ultra Low U-Values to 0.8 W/m²K.



- Quality laminated softwood construction.
- Slim profile styling.
- High security Secured by Design locking system fitted as standard.
- Manufactured from the finest FSC[®] accredited Redwood Nordic Pine timber.
- Extensive guarantees for long-lasting peace of mind.
- BRE Green Guide A+ Rated.
- Design enables window furniture to be concealed when viewed externally.
- Incorporating Swisspacer V, the leading warm edge spacer fitted SWISSPACER where appropriate.



TRADITIONALLY ELEGANT **SLIDING SASH WINDOW** RANGE

Superior quality and traditional design with built-in modern thermal performance

- Quality laminated Redwood Nordic Pine construction.
- Supplied fully finished.
- Can also be supplied to
 Secured by Design standard.
- Manufactured from FSC® accredited timber on request.
- Full chain of custody available
- Extensive guarantees for long-lasting peace of mind.
- Dual-sprung balances for ease of operation.
- BFRC B to C Rated.
- Low U-Values to 1.4 W/m²K.
- BRE Green Guide A+ Rated.
- Incorporating Swisspacer V, the leading warm edge spacer fitted SWISSPACER where appropriate.