

SF19

 ▶ Exceptional value multi-layer foil insulation

SuperFOIL Insulation

Thermal Insulation for use In
Roofs and Walls



**Local Authority
Building Control
Registered**

**U-value Solutions
as low as 0.1**

**Ideal for new build
or retrofit**

Roof

R 2.27

Wall

R 2.73

Floor

R 4.37



Quality System Manufactured to:
ISO 9001:2008



Meets the Requirements of Building Regulations Part L & BR443.
In accordance with EN16012; SuperFOIL is tested to BS EN 12667, ISO8301 by
British Board of Agrément, UKAS accredited laboratory

Key Features



- Tested 'R' Value 2.73
- Air seal & radiant barrier
- LABC Registered System

Find out more ▶

Technical



- Coverage 18.75m²
- Thickness 40mm
- Layers 19

Find out more ▶

Installation



- Horizontal or vertical fitting
- 25mm air gap required
- Cut with knife or scissors

Find out more ▶

SF19

SuperFOIL Insulation

Thermal Insulation for use in Roofs and Walls

Up to
R
2.73

Key Features

SF19 SuperFOIL has LABC Registered System Approval.

SF19 SuperFOIL has a BBA certified R value of 2.27 in pitch or flat roofs & 2.73 in walls.

Dupont ultra efficient nano coating technology.

SF19 SuperFOIL also acts as a radiant barrier to reflect excessive heat gain during the summer months as well as insulating throughout the year.

'DUET' Installation – An over and under the rafter application consisting of two layers of SuperFOIL. SF19 + SF40 provides a U-value of 0.18.

'COMBI' Installation – Use SuperFOIL with any other insulation including mineral wool or foam board to achieve any required insulation U-value.

SF19 SuperFOIL is ideal for use in walls and roof structures in new build and in renovation, refurbishment / extension projects.

SF19's technical specification means high performance from a small footprint.

Easy installation results in minimal waste. Superfoil is manufactured with 40% recycled materials and is recyclable at the end of its useful life.



Technical

DESCRIPTION

DESCRIPTION	LAYERS
Polypropylene reinforced heavy outer laminated foil	2
Aluminium coated reflective foil PET layers	6
Thermo foam separation layers	8
Loft quilt layers	3
Total layers	19
Packing	142 Poly tube
Weight per roll	13Kg
Dimensions packed	1.5m x 420mm

SPECIFICATION

SPECIFICATION	DATA
Certified 'R' value (ISO 8301)	2.73
Core 'R' value (BBA, ISO 8301)	1.31
Emissivity (ASTM C1371)	0.03
Water resistance (BS EN 20811:1992(1996) / BS 4016:1997 Annex B)	>1000cm / Pass
Tear strength (ISO 13937-2:1996)	Warp 515 N/50mm Weft 600 N/50mm
Fire Resistance (BS EN 11925-2:2005)	Class E (BS EN 13501-1:2007)
Thickness installed	40mm
Roll dimensions	1.5m x 12.5m
Total area per roll	18.75 sqm

Installation

Installing OVER rafters:

Roll out SF19 SuperFOIL over rafters. Staple at least 500mm or as conditions dictate and cover joints with SuperFOIL tape, overlap widths 75mm (Min 50mm Max 100mm)

At the eaves cut superFOIL around rafters and seal to cavity wall insulation or wall plate to create airtight envelope.

Fix battens parallel with the rafters and apply breathable roof underlay according to manufacturers guidelines.

Fix roofing battens & tiles according to manufacturers guidelines.

Installing UNDER rafters:

Roll out SuperFOIL, starting along the top of the roof. Batten horizontally over rafters. Staple at least 500mm or as conditions dictate and cover joints with SuperFOIL tape, overlap widths 75mm (Min 50mm Max 100mm).

At the bottom of the roof pitch, staple the SF19 SuperFOIL directly onto the timber wall plate to create airtight envelope.

Fix battens across the rafters and ensure air gap between SuperFOIL and the plasterboard.

SF19 Installers please note:

SF19 SuperFOIL can be used in all types of roof structure.

SF19 SuperFOIL can be laid horizontally or vertically depending on the characteristics of the area to be insulated.

SF19 SuperFOIL can be cut with a craft knife or scissors.

SF19 SuperFOIL is attached using galvanised or stainless steel staples.

Contact with lead, copper and its alloys should be avoided.

Do not use SF19 SuperFOIL to insulate a chimney flue.

When using SF19 SuperFOIL around downlighters a 30mm clear cavity must be provided. The use of fire rated fittings or fire hoods is recommended.

SF19 SuperFOIL is most effective with a 25mm minimum air gap easily provided with battens.

SF19 SuperFOIL should be stored under cover and protected from the elements.

SF19 SuperFOIL tape (20m x 100mm) to be used on all overlaps and joints.

Be careful of the sun's reflection when installing outside.

For more information visit www.SuperFOIL.co.uk

Sizes / figures are approximate and subject to change without notice, tolerance 1:0.01 to 1:0.15

Boulder Developments Ltd BHF, Norwell, Nottinghamshire, NG23 6JN
Tel:01636 639 900 Fax:01636 639 909 www.SuperFOIL.co.uk