

Safety & Security Film

100-Micron - Clear

Code: SA-100CL-iSR



Performance Data

Total Solar Energy

Transmitted	78%
-------------	-----

Reflected	9%
-----------	----

Absorbed	13%
----------	-----

Visible Light

Transmitted	86%
-------------	-----

Reflected	10%
-----------	-----

Ultra-Violet Rejected	<98%
-----------------------	------

Glare Reduction	N/A
-----------------	-----

Shading Coefficient	0.93
---------------------	------

Total Solar Energy Rejected	19%
-----------------------------	-----

Product Warranty	10 years
------------------	----------

Specification:


The safety & security window film is to be **SA-100CL-iSR**, as supplied by Partition Graphics (www.partitiongraphics.com). The film is to be installed to the **interior** surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.

(For exterior grade film also insert, **Exterior grade films must be correctly edge sealed**).

Notes:

Test results are produced from film applied to clear glass. Performance data is subject to change without prior notice. Accurate selection of window film requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct or consequential loss howsoever arising.

Solar Control Film
 Reflective - Silver 20 - External
Code: SO-20RS-eSR



Performance Data

Total Solar Energy

Transmitted	13%
Reflected	52%
Absorbed	35%

Visible Light

Transmitted	16%
Reflected	55%
Ultra-Violet Rejected	<99%
Glare Reduction	82%
Shading Coefficient	0.26
Total Solar Energy Rejected	78%
Product Warranty	7/4 years

Specification:

The solar control window film is to be **SO-20RS-eSR**, as supplied by Partition Graphics (www.partitiongraphics.com). The film is to be installed to the **exterior** surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.

(For exterior grade film also insert, **Exterior grade films must be correctly edge sealed**).

Notes:

Test results are produced from film applied to clear glass. Performance data is subject to change without prior notice. Accurate selection of window film requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct or consequential loss howsoever arising.