



DEMILEC APX

Breaking the boundaries of fire performance with revolutionary spray foam technology.

al allo

2014 Demilec. Reproduction of any information, graphics or statements in this brochure without prior written permission is strictly prohibited. This flyer is intended for general guidance and information only. No guaranty or warranty is intended or implied. Detailed information about our products, systems, installers and services is available from a representative in your area. For a list of representatives, visit www.DemilecUSA.com or call 1.877.DEMILEC (336-4532).





Demilec APX[™] is a revolutionary new open cell spray foam that can be sprayed in attics and crawl spaces without an ignition barrier or coating. Demilec APX is one of the few products that is compliant with the stringent test requirements of the International Code Council, without the use of additional fire protection products. Additionally, Demilec APX provides all of the traditional benefits you expect from spray foam including air sealing, lowering heating and cooling bills, helping reduce dust and allergens and contributing to a quieter indoor environment.

- AC 377 APPENDIX X COMPLIANT
- NO IGNITION BARRIER REQUIRED
- INSULATE & AIR SEAL IN ONE APPLICATION
- CALIFORNIA CA01350 LOW VOC COMPLIANT
- EXCELLENT ENERGY EFFICIENCY
- SUPERIOR PERFORMANCE & VALUE

Compliance Tested by Berkeley Analytical - Emission Testing Method for CA Specification 01350

Acceptance Criteria and Results Demonstrating Compliance of Product Sample to Referenced Standard:

•				
Exposure Scenario	Individual VOCs of Concern		Formaldehyde	
	Criterion	Compliant?	Criterion	Compliant?
School Classroom	≤½ Chronic REL	YES	≤ 9.0 µg/m³	YES
Private Office	≤½ Chronic REL	YES	≤ 9.0 µg/m³	YES
Single Family Residence	≤1⁄2 Chronic REL	YES	≤ 9.0 µg/m³	YES



Demilec 3315 E. Division Street Arlington, TX 76011 (817) 640-4900 (877) DEMILEC (336-4532) Info@Demilec.com www.DemilecUSA.com

