PRODUCT SPECIFICATION



GSW22P RENTAL



Indicative picture

		indicative picture
GENERATOR	GSW22P	Rental Kit includes
STANDBY POWER LTP KW/KVA	17.2/21.5	
PRIME POWER PRP KW/KVA	15.6/19.5	Socket - 1 x 415v 63amp;
VOLTAGE VOLT/FREQUENCY	400/50	
PHASES	3	Panel - 1 x 415v 32amp
ENGINE		- 3 x 230v 16amp
MANUFACTURER	Perkins	- hard wire facility
MODEL	4040-22G	
COOLING SYSTEM	Water	
FUEL	Diesel	Manual Analogue Panel
NUMBER AND DISPOSITION OF CYLINDERS	4 in Line	
DISPLACEMENT CC	2215	Fully Bunded Base
ASPIRATION	Natural	
STARTING SYSTEM/ELECTRIC CIRCUIT (VOLT)	Electronic / 12	
SPEED rpm	1500	Three Way Fuel Valves (to allow
SPEED GOVERNOR	Mechanical	connection to external fuel supply)
STAND BY POWER LTP kW	20.3	
PRIME POWER PRP Kw	18.4	Battery Isolator Switch
FUEL CONSUMPTION at 75% /100% prp L/h	4.0/5.3	
ALTERNATOR		
ТҮРЕ	Stamford	Single Key System
POLES	4	
VOLTAGE REGULATION SYSTEM	Electronic	
OVERALL DIMENSIONS AND WEIGHT		
LENGTH mm	1800	
WIDTH mm	850	
HEIGHT mm	1261	
WEIGHT Kg	755	
FUEL TANK CAPACITY L	78	
RUNNING TIME @ 75% / 100% PRP h	19.5/14.6	
NOISE PRESSURE LEVEL at 7mt dB(A)	61	
GUARANTEED SOUND POWER LEVEL LWA dB(A)	87	