

HYTRAC LIFTS LTD

GOODSMOVER GOODS LIFTS

WITH ATTENDANT

This lift range is a variation on the basic Goodsmover Lift and allows the goods being moved to be accompanied by a single trained operative.

A push station is fitted in the car which becomes active on the action of a keyswitch. The pushes are hold-to-run type and protection is given to the passenger through the use of a safety edge on the open side of the car. The car height is 2000mm and comes fitted as standard with a light and integrated emergency lighting. All other specification features and options are the same as the basic Goodsmover range.

Goodsmover with Attendant Standard Specification

- Self supporting galvanised steel structure designed to accept cladding
- Galvanised steel machine access door
- Inner shaft cladding on entrance side of structure
- Single hinged galvanised steel landing door on 500kg and small size 750kg models
- Double hinged galvanised steel landing doors on larger 750kg and 1000kg models
- 2000mm high galvanised steel car with wooden buffer rails
- Compact worm gear drive located inside the shaft at the top with chain drive arrangement
- Overspeed governor and safety gear arrangement designed to limit uncontrolled movement
- Microprocessor controller
- Car protection through use of safety edge
- Car light with integrated emergency lighting

Goodsmover with Attendant Options

- One side or open through entry configuration
- Low headroom option
- Bespoke car dimensions
- Zintec or stainless steel car finish
- Zintec or stainless steel landing door finish
- Zintec or stainless steel machine access door finish
- Single hinged door 2 hour fire-rated
- Galvanised structure cladding
- Overload device
- Aluminium checker plate floor

Electrical

- Additional auxiliary main contactor
- Phase failure reversal relay
- Landing push stations complete with car position indicator, lift in use indicator, door open signal and key isolator
- Keyswitch operated hold-to-run car push station with landing floor pushes, alarm button and emergency stop switch
- Lift arrival buzzer
- Anti-quick-reversal
- Overtravel timer
- Hand lamp
- Lift shaft lighting
- Light and socket within machine room
- Socket on car top and in pit
- Wiring in loom form

General

- Full set of warning notices
- User manual
- Comprehensive installer instructions
- Comprehensive UK style layout drawings and wiring diagrams
- Compliance with EC Machinery Regulations 2006/42/EC
- Carries the "CE" Mark





Goodsmove Goods Lifts With Attendant

BKG Type	500.15/49P	750.15/49P	750.15/50P	1000.15/50P
Rated Load (kg)	500	750	750	1000
Speed (mps)	0.15	0.15	0.15	0.15
Hinged Landing Door	Single	Single	Double	Double
Standard Car Width (mm)*	1000	1000	1300	1300
Standard Car Depth (mm)*	1400	1400	1700	1700
Standard Car Height (mm)*	2000	2000	2000	2000
Standard Shaft Width (mm) Single Entry	1515	1515	1825	1825
Standard Shaft Depth (mm) Single & Though Entry	1630	1630	1940	1940
Headroom (mm)	3400	3400	3300	3300
Pit (mm)	170	170	170	170

* Bespoke car dimensions available on request. Please check with Shorts.

** Reduced headroom model (2700mm) available on request