


Automatic Rewind Machine



Specification

- ❑ Maximum parent roll width 600mm (24") Diameter 500mm (20")
- ❑ Accepts parent rolls on 76mm (3") I.D. cores.
- ❑ Master roll lifting table.
- ❑ Variable speed drive of up to 1000m per minute.
- ❑ Programmable electronic length counter.
- ❑ Automatic core feed hopper.
- ❑ Single turret rewind arm.
- ❑ Automatic film cut off & attachment.
- ❑ Rewind roll maximum diameter 150mm (6").
- ❑ Rewind core diameter from 76mm (3") to 25mm (1") with change parts.
- ❑ Finished roll storage table. (Other options available including conveyor systems and auto-rack storage)
- ❑ 3 - phase 220-400 volt 50-60Hz supply. / Air requirements - 4 cfm max. at 80 psi.
- ❑ Totally enclosed interlocked guarding ensuring maximum operator safety.



CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England
Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com