

Automatic 'Hand & Band' Rewind Slitting Machine



Specification

- ❑ Maximum parent roll width 760mm (30") Diameter 500mm (20")
 - ❑ Accepts parent rolls on 76mm (3") I.D. cores.
 - ❑ Master roll lifting table.
 - ❑ Nine adjustable slitting blades
 - ❑ Interchangeable steering units for a variety of web widths.
 - ❑ Rewinding capability from full width to 76mm (3").
 - ❑ Capability of rewinding 1" id extended cores, (20" film on 30" cores).
 - ❑ Adjustable external electronic rewind tension from **-3% to +5%** in increments of **0.1%**
 - ❑ Variable speed drive of up to 1000m (3000') **per minute**.
 - ❑ Programmable electronic length counter.
 - ❑ Automatic core feed hopper.
 - ❑ Single turret rewind arm.
 - ❑ Automatic film cut off & attachment.
 - ❑ Rewind roll maximum diameter 150mm (6") maximum core width 810mm (32"). Minimum core width 82mm (3.25")
 - ❑ Rewind core diameter from 76mm (3") to 25mm (1") with change parts.
- ❑ Finished roll storage table. (Other options available including conveyor systems and auto-rack storage)
 - ❑ 3 - phase 220-400 volt 50-60Hz supply. / Air requirements - 4 cfm max. at 80 psi.
 - ❑ Totally enclosed interlocked guarding ensuring maximum operator safety.



Converting Equipment Ltd

CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England

Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators &
Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com