

Automatic 'Handywrap' Mini Roll Slitter Rewinding Machine



Specification

- ❑ **Maximum parent roll width 500mm (20") Diameter 500mm (20") for full width finished roll production**
- ❑ Maximum parent roll width 400mm (16") Diameter 500mm (20") for Handywrap/mini roll production
- ❑ **Accepts parent rolls on 76mm (3") I.D. cores.**
- ❑ Master roll lifting table.
- ❑ **Variable speed drive of up to 1000m per minute.**
- ❑ Programmable electronic length counter.
- ❑ **Automatic core feed hopper.**
- ❑ Single turret rewind arm.
- ❑ **Automatic film cut off & attachment.**
- ❑ Rewind roll maximum diameter 150mm (6").
- ❑ **Rewind core diameter from 76mm (3") to 25mm (1") with change parts.**
- ❑ Finished roll storage table. (Other options available)
- ❑ **3 - phase 220-400 volt 50-60Hz supply.**
- ❑ Air requirements - 4 cfm max. at 80 psi.
- ❑ **Totally enclosed interlocked guarding ensuring maximum operator safety.**



CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England
Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators &
Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com