

Fully Automatic 'Hollowrap' Slitter

Specification

- ❑ Maximum parent roll width **20"** (500mm)
- ❑ Maximum parent roll diameter **20"** (500mm)
- ❑ Accepts parent rolls on **3"** (76mm) I.D. cores.
- ❑ Master roll lifting table.

- ❑ **Six** adjustable slitting blades
- ❑ Interchangeable steering units for **3", 5" and 10"** web widths.
- ❑ **Full** width rewinding capability.

- ❑ Adjustable external electronic rewind tension from **-3% to +5%** in increments of **0.1%**
- ❑ Variable speed drives giving a machine capability of up to **3000'** (1000 m) **per minute**.
- ❑ Programmable electronic **length counter**.
- ❑ **HMI** control panel.
- ❑ Film break sensors
- ❑ Patented Hollowrap™ Rewind **Mandrels**
- ❑ Automatic single **twin turret** rewind arm.
- ❑ Automatic **film attachment**.
- ❑ Automatic **film cut off**.
- ❑ Automatic finished **roll unloading**

- ❑ Rewind roll maximum diameter **8.5"** (220mm)
- ❑ Finished roll return **exit conveyor**.

- ❑ 3 - phase 220-400 volt 50-60Hz supply. / Air requirements - 4 cfm max. at 80 psi.



CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England
Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com