

Fully Automatic Triple Turret Slitter Rewinder

TT1000 SR

****Cored or Coreless production****

Specification

- ❑ Maximum parent roll width 1000mm (40")
- ❑ Maximum parent roll diameter 500mm (20")
- ❑ Accepts parent rolls on 76mm (3") I.D. cores
- ❑ Master roll lifting table
- ❑ Master roll lateral film adjustment
- ❑ Film break sensors

- ❑ HMI control panel
- ❑ Rewind length programmed on the front control panel.
- ❑ Programmable electronic length counter
- ❑ Variable speed drive
- ❑ Servo driven rewind.
- ❑ Slitting blades for multiple finished roll winding *(with change parts)*



- ❑ Automatic triple turret rewinding head including:
 - ❑ Automatic core hopper
 - ❑ Automatic multi-core loading
 - ❑ Automatic film attachment
 - ❑ Automatic film cut off
 - ❑ Automatic finished roll unloading
 - ❑ Rewinding capability from 250mm (10") to full width *(with change parts)*
 - ❑ Rewind maximum diameter 250mm (10")
 - ❑ Rewind Mandrels for 60mm to 76mm cores fitted *(to be specified on order)*
 - ❑ Rewind Mandrels for 60mm to 76mm coreless fitted *(to be specified on order)*
 - ❑ Finished roll collection table *(other options available)*
- ❑ 3 - phase 380-440 volt 50-60Hz supply.
- ❑ Air requirements - 4 cfm max. at 80 psi

[CG Automatic Converting Equipment Ltd](#)

8 Highmeres Rd
Leicester LE4 9LZ
England

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.

Ph +44 116 2760206

Fax +44 116 2742995

sales@cga-converting.com / www.cga-converting.com