

Auto-Prestretch Rewinding Machine 600mm or 1m wide versions both can be fitted with a straight rewinder option



Specification

- ❑ Maximum parent roll width 600mm or 1m. (24" or 40")
 - ❑ Maximum parent roll diameter 500mm. (20")
 - ❑ Accepts parent rolls on 76mm (3") I.D. cores.
 - ❑ Master roll lift table
 - ❑ Lateral film adjustment & optional oscillation.
 - ❑ Rewind stretch ratio programmed on the front control panel.
 - ❑ Four roller stretcher train geared to give a fixed stretch ratio of 335%.
 - ❑ Servo driven rewind to vary final tension from 150% to 300%.
 - ❑ Variable speed drive giving a machine capability of up to 550 metres (1700') per minute.
 - ❑ Programmable electronic length counter.
 - ❑ Automatic core feed hopper & core loading.
 - ❑ Single position turret rewind arm.
 - ❑ Automatic film cut off & film attachment.
 - ❑ Non contact film break sensor.
 - ❑ Rewind roll maximum diameter 220mm (8.5")
 - ❑ Rewind core diameter 38mm (1.5"), 50mm (2"), 76mm (3") (to be specified on order).
 - ❑ Capability of slitting and rewinding.
- ❑ Finished roll storage table. Other options available including conveyor systems and auto-rack storage
 - ❑ 3 - phase 220-400 volt 50-60Hz supply. / Air requirements - 4 cfm max. at 80 psi.
 - ❑ Totally enclosed interlocked guarding ensuring maximum operator safety.
 - ❑ Multi option finished roll production. Soft roll tight roll or oscillated roll



CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England

Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators &
Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com