

# Fully Automatic Triple Turret Prestretch Rewinder

TT1000 Auto Stretcher

## Specification

- ❑ Maximum parent roll width 1000mm (40")
- ❑ Maximum parent roll diameter 500mm (20")
- ❑ Accepts parent rolls on 76mm (3") I.D. cores
- ❑ Master roll lifting table
- ❑ Master roll lateral film adjustment
- ❑ Film break sensors
  
- ❑ HMI control panel
- ❑ Rewind stretch ratio programmed on the front control panel.
- ❑ Programmable electronic length counter
- ❑ Variable speed drive (up to 600m 2000' per minute)
- ❑ Servo driven rewind to vary final tension from 150% to 300%.
- ❑ Slitting blades for multiple finished roll winding *(with change parts)*



- ❑ Automatic triple turret rewinding head including:
  - ❑ Automatic core hopper
  - ❑ Automatic multi-core loading
  - ❑ Automatic film attachment
  - ❑ Automatic film cut off
  - ❑ Automatic finished roll unloading
  
- ❑ Rewinding capability from 250mm (10") to full width *(with change parts)*
- ❑ Rewind maximum diameter 250mm (10")
- ❑ Rewind Mandrels for 50mm to 76mm cores *(to be specified on order)*
- ❑ Finished roll collection table *(other options available)*
  
- ❑ 3 - phase 380-440 volt 50-60Hz supply.
- ❑ Air requirements - 4 cfm max. at 80 psi

**Multi-option finished roll production.** Tight, soft or 'super soft' roll, oscillated or non oscillated roll, edge guided or non edge guided rolls  
Or any combination of these!



[CG Automatic Converting Equipment Ltd](#)

8 Highmeres Rd  
Leicester LE4 9LZ  
England

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.

Ph +44 116 2760206 Fax +44 116 2742995

[sales@cga-converting.com](mailto:sales@cga-converting.com) / [www.cga-converting.com](http://www.cga-converting.com)