

# Semi-Automatic Hollowrap™ Coreless Rewinding Machine

A semi-automatic machine primarily designed for the conversion of stretch film in to Coreless Hand Rolls

## Machine Specification

- Front Loading master rolls
- Master roll width from 250mm (10") to 500mm (20")
- Master roll diameter up to 500mm (20")
- Master roll core diameter 76mm (3")
- Manually adjusted pneumatic master roll and collet pressure
- Supplied with one patented 60mm Hollowrap™ mandrel to allow coreless winding  
(Different size mandrels can be added to suit your requirements).
- Variable rewinding speed up to 600m (2000') per minute
- Multi-Servo controlled, variable tension, drive system.
- Electronic adjustment of web tensions.
- Programmable counter for precise rewind length and braking control.
- Manually adjusted pneumatic rewind pressure
- Maximum rewind roll diameter 140mm (5 1/2")
- 220 or 400V 3 phase models.
- Guarding to C.E. regulations.



**Handles and Dispensers for 60mm products also available.**



[CG Automatic Converting Equipment Ltd](#)  
8 Highmeres Rd  
Leicester LE4 9LZ  
England  
Ph +44 116 2760206 Fax +44 116 2742995  
[sales@cga-converting.com](mailto:sales@cga-converting.com) / [www.cga-converting.com](http://www.cga-converting.com)

**Designing, Manufacturing & Supplying**

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.