RCP/2 Non woven slitter perforator.

The RCP/2 has been primarily designed to slit and perforate non woven materials, although it is also suitable for many other materials such as wrap films and foams. The machine unwinds the material, slits it to the desired widths, cross perforates it to the preset pitch distance and rewinds it either coreless or on to its new core.



Specification.

- □ Variable speed control from 0 to 100 metres per min slitting / perforating. (up to 200 metres per minute slitting only).
- □ Maximum roll diameter 1000mm.
- □ Available as standard roll widths of, 1.6m, 2.1m & 2.6m (other widths available on order.)
- □ Servo controlled variable perforating pitch from 150mm to 6000mm
- □ Adjustable slitting, crush cut, shear cut or razor cutting (state on order).
- Easy adjustment of perforation depth
- □ Accurate and reliable perforation distances
- □ Compact and ergonomic design
- □ Supply 3-phase 415 volts 20 amps max.
- □ Air supply 6 bar
- □ Guarding to suit C.E requirements

Machine Features.









Adjustable crush cut station.

Perforation anvil.

Easy tear perforation on roll.

Cantilever unwind.



CG Automatic Converting Equipment Ltd 8 Highmeres Rd Leicester LE4 9LZ England Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com