



R34000  
 Typical Pick Radius  
 Gross Capacity 61t  
 (0t derrick counterweight)

R50000  
 Gross Capacity 29.7t  
 (0t derrick counterweight)  
 Gross Capacity 59t  
 (up to 150t derrick counterweight)

R28000  
 Gross Capacity 73t  
 (0t derrick counterweight)

R42000  
 Gross Capacity 40.5t  
 (0t derrick counterweight)

R43000  
 Gross Capacity 61t  
 (0t derrick counterweight)

- Notes:
1. Ground affected by crane must level and well-compacted to withstand given ground bearing pressures.
  2. Max allowable windspeed = 11.1 m/s.

RAILWAY

Road Edge

Concrete Slab Access Road

Concrete Slab Access Road

Concrete Slab Access Road

Concrete Slab Access Road

Concrete Slab Access Road

Derrick tray radius

See Notes

Typical Delivery Position

Typical Rigging Crane Positions

Sloping Verge

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap

Spoil Heap