Tubular Solenoid



Long Life Linear

Push SDT2039S-2XX Pull SDT2039L-2XX

- Dielectric Strength: 1000 VRMS
- Recommended Heat Sink: Maximum watts dissipated by the solenoid are based on an unrestricted flow of air at 20°C mounted on the equivalent of an aluminium plate 76 x 76 x 3.2mm min.

General Specifications:

- Coil Resistance: +/- 5% tolerance
- Holding Force: 12.8 N @ 20°C
- Weight: 74.9 g Pull / 78.2 g Push
- Plunger Weight: 18.0 g Pull / 13.5 g Push

250 MIN

Solenoid shown in energised position

39.37 MAX

9.52±0.30


Notes

- 1. Continuously pulsed at stated watts and duty cycle
- Single pulsed at stated watts (with coil at ambient room temperature 20℃)
- Other coil gauges available, consult factory
- 4. Reference number of turns
- 5. Anti rotational mounting bushes available on request

R28.6 MIN Ø2.60 19.05±0.38 Ø19.56 MAX 39.37 MAX 4.76±0.30 9.52±0.30 2.60 Ø7.82 ±0.08 Ø2.39±0.08 3388 M14 x 1.5 50±0.30 NIM AWG, P.V.C. 250 I

Performance Specification

Typical Starting Force @ 20 ℃



How to Order

Add the coil awg. number to the part number, alternatively please specify:

- Voltage
- Duty Cycle
- Starting Force
- Stroke Required
- Any Special Requirements

Coil Specifications

M14 x 1.5

Maximum Duty Cycle	100%	50%	25%	10%
Maximum ON Time (seconds) When pulsed continuously (1)	∞	230	25	6
Maximum ON Time (seconds) for single pulse (2)	∞	265	63	15
Watts (@20°C)	7	14	28	70
Ampere Turns (@ 20° C)	855	1200	1700	2700

Coil Data

28.58±0.38

awg. (2XX) (3)	Resistance (@ 20℃)	# Turns (4)	Nominal DC Voltage				
25	2.13	488	3.9	5.5	7.7	12.2	
26	2.9	544	4.5	6.4	9.0	14.2	
27	5.27	760	6.1	8.6	12.1	19.2	
28	9.15	1026	8.0	11.3	16.0	25.0	
29	12.5	1146	9.4	13.2	18.7	30.0	
30	20.7	1491	12.0	17.0	24.0	38.0	
31	33.6	1904	15.0	22.0	31.0	48.0	
32	53.5	2394	19.4	27.0	39.0	61.0	
33	83.5	2970	24.0	34.0	48.0	76.0	

Please Note: In line with continued development we reserve the right to amend specification without prior notice (Rev 01/12)

NSF Controls Ltd | Ingrow Bridge Works | Keighley | West Yorkshire | BD21 5EF | UK | Registered in England No. 3378269