## **ATEX Ventilation**







## 16"/40cm | AFi50xx Intrinsically Safe Air Driven Blower/Exhauster

- Intrinsically safe for use in adverse atmospheres
- Pneumatic powered blower
- Precision balanced, cast aluminum turbo impeller
- High Strength, anti-static glass reinforced ABS housing is lightweight, corrosion proof and chemical resistant
- Integral 16"/40cm duct adapters
- Exhausts OUTSIDE of duct, compressed air not in airstream
- Complete with filter, motor lubricator, exhaust muffler, air control valve and static grounding cord
- IMPA Codes: AA7000 - 591512, 591426

Optional Accessories: Standard Duct, Anti-Static Duct, Duct Carrying Bags, Cooling Collar, 16"/40cm Multi-Purpose Accessory Pack, Door Bar and Hanger Kit

MODEL	AFi50xx
Order #	AA7000
FREE AIRFLOW*	3,200cfm/5,440m³/hr
AIR CONSUMPTION	40cfm/68m³/hr
INDUCTION RATIO	80:1
WEIGHT	43lbs/20kg
DIMENSIONS (h/w/d**)	19/21/12 in 480/530/305 mm
NOISE	89dB
MOTOR	GAST 4AM-NRV-50C

<sup>\*</sup> Measurements @ 80psig inlet air



## The Complete Supply Solution

<sup>\*\*</sup>Add 2 in/51 mm to depth per attached duct adapter