






## 12" / 30cm | EFi75xx Intrinsically Safe Blower/Exhauster

- Intrinsically safe – ATEX certified for use in adverse atmosphere
- Cast aluminum turbo blade is precision balanced
- Tough, chemical resistant ABS housing, carbon-filled to conduct static charges to ground
- IP65 rain tested switch enclosure "watertight"
- Integral 12"/30cm duct adapters
- Blow or exhaust hazardous/explosive gases safely
- Uses 12"/30cm or 8"/20cm duct, (8"/20cm requires optional adapter) conductive or non, suction or discharge
- Call for plug options – see page 46 for chart
- IMPA Codes:  
EB7201xx (110V) - 591506, 591418, 591423  
EB7201xx-230 (230V) - 591506, 591419, 591424



MODEL	EFi75xx	
Order #	EB7201XX/EB7201XX-230	
FREE AIRFLOW	2,500cfm/4,250m <sup>3</sup> /hr	
15ft/1-90° turn	1,664cfm/2,829m <sup>3</sup> /hr	
15ft/2-90° turns	1,529cfm/2,599m <sup>3</sup> /hr	
WEIGHT	44lbs/20kg	
DIMENSIONS (h/w/d)	16/15/16 in 406/381/406 mm	
NOISE	89dB	
MOTOR	0.75Hp/0.56kW	
ELECTRIC	115/230VAC, 1ø, 50/60Hz	
AMPS – START – RUN	115V: 37A    230V: 27A 115V: 7.2A    230V: 3A	
UNIT CERTIFICATION	 II 2 G Ex de IIB T6  BR-Ex de IIB T6	
MOTOR CERTIFICATION	 II 2 G Ex d IIB	

Optional Accessories: Anti-Static Duct, Duct Carrying Bags



# The Complete Supply Solution