



[www.RylardBoats.com](http://www.RylardBoats.com)

# Technical Data Sheet

**PRODUCT NAME:** **WOOD PRIMER-GREY**

---

**CODE NUMBER:** A 2303-R1

---

**PRODUCT DESCRIPTION:** Brushing and spraying primer for use on all wooden surfaces.

---

**PERFORMANCE/USE:** Primer containing high quality fillers to give excellent sealing and filling of solid and plywoods used in boat construction. Formulated as part of the total Rylard system, the primer is ideal as the base for subsequent finishing with Rylard undercoat and Rylard Plus Enamel.

---

**SURFACE PREPARATION:** Ensure all surfaces are clean and free from dirt. Sand wood surface with minimum final 120 grit sand paper.  
Refer to our painting hints booklet before starting work.

---

**APPLICATION:** Apply by brush, roller or spray.  
**On marine ply:** thin 1<sup>st</sup> coat with equal parts Ry-thin thinners to ensure correct sealing of ply surface.  
**For solid woods/subsequent primer coats:** use as supplied; thin as required with Ry-thin thinners; recommended addition 5-10% dependent upon spray equipment.  
Minimum application temperature: 10°C

---

**DRYING/OVERCOATING:** Touch/dust dry(15°C) 30 minutes -1 hour  
Hard dry/Overcoating(15°C) 16-24 hours

---

**PHYSICAL PROPERTIES:**

Supply Viscosity	2500CPS
Supply SG	1.320
Colour	Light Grey
Theoretical Coverage:	10-12 square metres per litre per coat
VOC Content:	430 grammes per litre
Flash Point / Class / UN No	≥32°C & ≤55°C / III / UN 1263
Pack Size	750ml and 2.5 litre containers
Shelf Life	24 months unopened, stored at UK ambient temperatures.
Health & safety:	Refer to Product Safety Data Sheet before use.

*This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department,*

**Distributed by:**  
**Mainline**  
2 Sefton Road  
Litherland  
Liverpool L21 7PG  
Tel: 0151 920 6451  
Fax: 0151 920 6452

**Your Local Stockist:**