



www.RylardBoats.com

Technical Data Sheet

PRODUCT NAME: RYTEX

CODE NUMBER: 40033

PRODUCT DESCRIPTION: Versatile high performance bodied bitumen solution which dries to an attractive satin finish.

PERFORMANCE/USE: Formulated for water immersion conditions, Has good abrasion and weather resistance, thus providing a longer life than conventional bitumen coatings. The bodied solution makes for easy application.

SURFACE PREPARATION: **New Work:** Clean/de-rust to bright metal. Abrade with coarse wet & dry. Degrease. **Refurbishment:** Pressure clean; de-rust as required and patch treat before full application.

APPLICATION: Apply by brush; roller or airless spray. Use as supplied; thin if required with White Spirit.. Apply 3 coats on new work; 1-2 coats on refurbishment
Minimum application temperature: 10°C

DRYING/OVERCOATING:	Drying time(10°C)	6-8 hours
	Overcoating time(10°C)	24 hours
	Launch time(10°C)	48 hours

PHYSICAL PROPERTIES:	Mixing Ratio	Single pack product
	Thinner/Cleaner	White Spirit
	Supply Viscosity	2600 cps
	Supply SG	1.10
	Colour	Black
	Gloss Level	Satin
	Theoretical Coverage:	4 square metres per litre per coat
	VOC Content:	410 grammes per litre
	Flash Point / Class / UN No	≥32°C & ≤55°C / III / UN 1263
	Pack Size	5 & 20 litre containers
	Shelf Life	12 months unopened, stored at UK ambient temperatures.
	Health & safety:	Refer to Product Safety Data Sheet before use.

This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department,

Distributed by:
Mainline
2 Sefton Road
Litherland
Liverpool L21 7PG
Tel: 0151 920 6451
Fax: 0151 920 6452

Your Local Stockist: