



[www.RylardBoats.com](http://www.RylardBoats.com)

# Technical Data Sheet

**PRODUCT NAME:** **PREMIUM PROTECTION**

**CODE NUMBER:** 40032

**PRODUCT DESCRIPTION:** High performance bitumen coating containing Gilsonite and synthetic resins. Exhibits a deep black gloss finish. Suitable for application to iron & steel and weathered masonry.

**PERFORMANCE/USE:** Has excellent weather resistance, abrasion resistance, allied to a degree of oil & diesel resistance. Will have a longer life than conventional bitumen coatings. Easily applied, makes an ideal refresher coat over any narrow boat bottom blacking.

**SURFACE PREPARATION:** **New Work:** Clean/de-rust to bright metal. Abrade with coarse wet & dry. Degrease. **Refurbishment:** Pressure clean; de-rust as required and patch treat before full application.

**APPLICATION:** Apply by brush; roller or airless spray. Use as supplied; thin if required with White Spirit.. Apply 3 coats on new work; 1-2 coats on refurbishment  
Minimum application temperature: 10°C

**DRYING/OVERCOATING:**

Drying time(10°C)	6-8 hours
Overcoating time(10°C)	24 hours
Launch time(10°C)	48 hours

**PHYSICAL PROPERTIES:**

Mixing Ratio	Single pack product
Thinner/Cleaner	White Spirit
Supply Viscosity	240 Seconds/ISO 6 Cup/23°C
Supply SG	0.92
Colour	Deep Black
Gloss Level	Gloss
Theoretical Coverage:	8 square metres per litre per coat
VOC Content:	440 grammes per litre
Flash Point / Class / UN No	≥32°C & ≤55°C / III / UN 1263
Pack Size	5 & 20 litre containers
Shelf Life	12 months unopened, stored at UK ambient temperatures.
Health & safety:	Refer to Product Safety Data Sheet before use.

*This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department,*

**Distributed by:**  
**Mainline**  
2 Sefton Road  
Litherland  
Liverpool L21 7PG  
Tel: 0151 920 6451  
Fax: 0151 920 6452

**Your Local Stockist:**