Uniflo Products Ltd

Sanitary Waste Pumps



Information Sheet Uniflo-Flush 4 macerator

The Uniflo-Flush/4 is a quality product it comes complete with the standard WC inlet, a top left inlet, and a further two additional low level inlets to accommodate other bathroom fixtures ie: shower, basin, bidet (please note: the Uniflo-flush/4 is not suitable for a bath and some old type washing machines) any of the inlets can be blanked off if not needed making this unit ideal for any type of installation. This unit has built in non-return valves as standard. The waste pumped outlet can be installed in 32, 28 or 22mm pipe work, a 90deg long radius elbow is supplied to accommodate all three sizes.

The macerator is fully automatic, it has a powerful 400w motor. The compact and modern design will blend in with any bathroom installation, it also includes easy access for servicing, making this product your first choice in waste removal.

Warning !!! Please do not put foreign objects through the unit, it will cause blockages and damage. Please refer to the, Waste Pump for Toilets Booklet.

IDEAL FOR CELLAR AND BASEMENT CONVERSIONS. Please Note: This Product is not suitable for Baths.







Input Voltage AC 220-240v, 50hz Input Power 400w Protection IPX4 Max Input Flow: 14.5L / min Output flow 240L / min

Technical Data:

The Macerator unit is designed to grind up and pump away sanitary waste from toilets and bathroom fixtures.

The unit works on pressure, when the toilet is flushed or a basin / shower is used the waste water enters the unit causing the pressure to build up inside the pressure chamber, this then activates the motor and pump which drives the cutting blades to grind up the waste and pump the liquid through the outlet via small bore pipe work to the sewer or soil stack, making it possible to install a bathroom virtually anywhere in the home.

info@unifloproducts.co.uk www.unifloproducts.co.uk

