

CI Sfb	E
(31.5)	

# **CLEARVIEW GLAZED OVERHEAD DOORS**

Filling the need in many appllications such as service stations, tyre bays and where extra light or a picture window effect is required, the Clearview overhead door combines a smart clean appearance with long lasting visual appeal. Clearview is a glazed overhead door formed from a series of hinged extruded anodised aluminium rails & stiles



## **Clearview Colour**

As an option the Clearview door can be supplied with its frame and any insulated sections in a Ral colour finish

### **Track System**

The position of the door in a building may require that a specific track configuration is used to optimise the free space above the door. We recommend that the space between the door tracks and the roof is kept to a minimum ( exact dimensional details available on request or see on www.avondoors.co.uk)

#### **Options**

Electric operation Integral pass doors Remote Controls Safe edges Glazing types Matching fascias Colour finish Exhaust ports



As standard Clearview doors are double glazed using 2.5mm thick acrylic glass clear material, other forms of glazing are available. The bottom section of the door is an insulated section with heavy duty foot plate handle and double edged neoprene weather seal. Locking is by spring loaded shoot bolt



NEW 'No Stile' Glazed Overhead Door

## **Health & Safety:**

All doors produced conform to current UK regulations as well as EN 13241-1. Products are CE marked, certificates and operating manuals are available

Avon Industrial Doors Ltd, Armstrong Way, Gt Western Business Park, Yate , Bristol, bs375ng

Tel: 01454 273110 Fax: 01454 323224

Email: sales@avondoors.co.uk web site www.avondoors.co.uk