## **Carbon Steel Fittings Range**

PK Hydraulics offer an extensive range of standard carbon steel fittings treated with Trivalent Passivate .The fittings are suitable for use with both fluid and gas applications in the Oil and Gas, Hydraulics and renewable industries. All fittings are sourced in the UK and are fully 9001 and UKAs approval.

Our range is available in various connection sizes and combinations to meet the varying needs of our customers. The standard connections include BSPP, BSPT, SAE, NPT and JIC are available male to male, female to female and male to female. In addition to the standard fittings available from stock we are able to supply bespoke fittings to meet customer Requirements at minimum lead times and very competitive prices.

We can offer a next day delivery service to most of the UK mainland and due to our location near Aberdeen international airport are able to serve our overseas customers.

FLARED FITTINGS: Produced to SAE J514 standard. Elbows and tees forged construction. Working pressure 5000psi subject to tube size											
Dash No	4	5	6	8	10	12	14	16	20	24	32
Tube No	1/4	5/16	3/8	1/2	5/8	3/4	7/8	1	1.1/4	1.1/2	2
Straight Thread	7/16-20	1/2-20	9/16-18	3/4-16	7/8-14	1.1/6-12	1.3/16-12	1.5/16-12	1.5/8-12	1.7/8-12	2.1/2-12

ORFS FITTINGS: Produced to SAE J514 standard. Elbows and tees forged construction. Working pressure 6000psi subject to tube size												
Dash No	Dash No 4 6 8 10 12 16 20 24											
Tube No	1/4	3/8	1/2	5/8	3/4	1	1.1/4	1.1/2				
Straight Thread	7/16-20	1/2-20	9/16-18	3/4-16	7/8-14	1.1/6-12	1.3/16-12	1.5/16-12				

NPT FITTINGS: Produced to SAE J514 standard. Elbows and tees forged construction. Working pressure to tube size										
Dash No	2	4	6	8	12	16	20	24	32	
Tube No	1/8	1/4	3/8	1/2	3/4	1	1.1/4	1.1/2	2	
Straight Thread	7/16-20	1/2-20	9/16-18	3/4-16	7/8-14	1.1/6-12	1.3/16-12	1.5/16-12	1.5/8-12	

BSPP FITTINGS: Elbows and tees forged construction. Pressure rating below not applicable to swept bends												
INS	NS 1/8 1/4 3/8 1/2 9/16 5/8 3/4 1 1.1/4 1.1/2 2 2.1/2											2.1/2
Design Working Pressure	350	450	380	310	289	280	240	210	170	136	136	84
Proof Pressure	525	675	570	465	434	420	360	315	255	204	204	126



Emergency 24/7 Tel: 03300227077 Tel: 01224 249600 Fax: 01224 870701