



TECHNICAL DATA SHEET – NU-FLAME SINGLE COLOUR COATING SYSTEM

DESCRIPTION:

Nu-Flame is a smooth, non-flammable, water soluble, single-colour coating system, providing a durable and protective finish to previously painted internal surfaces.

ADVANTAGES:

Upgrades existing painted surfaces to Class '0'
Optional graffiti resistant finish Water based for minimum hazard during application **Tested to BS 476 part 6 & 7 and satisfies Class '0' requirements of current Building Regulations.**

USES:

Internal decorative paint system.

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS

	SP Tack Primer	Heat Insulating Basecoat	FR Colourcoat
COLOUR	White	Off white	Any RAL / BS4800 Colour
PACK SIZE	5 Litres	5 Litres	5 Litres
COVERAGE	14 m ² /litre	8 m ² /litre 2 coats	12 m ² /litre
DRYING TIME	4 Hours	4 Hours	4 Hours

Unit 7 Phoenix Road
Wednesfield
Wolverhampton
WV11 3PX
TEL: +44(0) 1902 450950

