



## TECHNICAL DATA SHEET – HPC 111 NU-FLAME FR ACRYLIC EGGSHELL

### DESCRIPTION:

Nu-Flame Acrylic F.R. Eggshell is a water based flame retardant paint for new and previously painted surfaces, timber and concrete where an eggshell finish is required.

### ADVANTAGES:

When Nu-Flame Acrylic F.R. Eggshell is used it provides a washable finish for interior use. Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations

### USES:

For use on doors, skirting and other timber finishes as well as painted surfaces and concrete to complement the Nu-Flame wall finishes

### COLOUR RANGE:

In any BS400 or RAL Shade.

### PACK SIZE:

Single component product, supplied in 5 & 10 litre units.

### COVERAGE RATE:

14 m<sup>2</sup> per litre

### VOLUME SOLIDS

40%

### DRYING TIME:

Touch: 2 Hours  
Overcoat: 6 Hours

### PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

### APPLICATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Abrade to provide a key.

### EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

### STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS

Unit 7 Phoenix Road  
Wednesfield  
Wolverhampton  
WV11 3PX

TEL: +44(0) 1902 450950

