

## Bi-Fold (sliding-folding) system

### Exterior

There are no obstacles here. You don't need to move any plants or standard lamps, because the door panels fold outwards, creating an opening up to 25/7.7 meter wide and 9'/2.8 meter high.

And a nice benefit: If you open the door after a rain shower, the water automatically drains to the outside – leaving everything dry inside.

#### Exemplary durability

The bi-fold door perfectly demonstrates the stable and durable nature of UNILUX's products. Aluminium is used as the base material and wood as the cladding, creating a high degree of rigidity in one element, in which everything fits perfectly together.

#### Freedom of design

Easy on the eye: The bi-fold door comes in wood species, contours, wood colors and external colors which blend seamlessly into the UNILUX aluminium clad wood window line (including energy saving triple-pane glass).

Even the external handle can be matched to the unit's exterior color. And upon request, the bi-fold door is also available with embedded threshold.





### Seamless connection

Depending on the architecture, the panels' castors can be integrated into the floor – forming the basis for a flat sill track and fluid transition.



### Freedom of interior design

As the panels open outwards, you don't need to create any space for them inside. And when they are opened, raindrops land on the terrace instead of the floor.



### Handles

Practical when you want to get out quickly. Depending on how the elements are divided, a standard door handle can be installed (in the same color as the element's exterior).