

T084 Eco Wax

An excellent eco wax quality offering optimum cost benefits. This high quality ribbon covers all general purpose requirements expected from a wax ribbon for a solid performance on paper substrates. It provides clear, crisp barcodes – standard, rotated or 2-D on a variety of paper label stocks. The back coat has a very low friction co-efficient and contains an anti-static additive to prolong the life of the print head.

General Item Data		
Film Thickness	:	4.5µm
Print Speed	:	8" = 200mm/s
Print Energy	:	Low - Medium

Substrate Application Range			
Vellum	✓	Tag Board	✓
Uncoated	✓	Matt Coated	✓
Semi Gloss	✓	Gloss Coated	✓

Characteristics Level										
Chemical Resistance	1	2	3	4	5	6	7	8	9	10
Durability	1	2	3	4	5	6	7	8	9	10
Substrate Versatility	1	2	3	4	5	6	7	8	9	10
Print Energy	1	2	3	4	5	6	7	8	9	10
Print Speed	1	2	3	4	5	6	7	8	9	10

Revision B

1 = Low 10 = High

These tests are performed using standard Pelikan test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.



Conforms to REACH (1907/2006/EC) RoHS (2011/65/EU) & WEEE 2002/96/EG. Material Safety Data Sheets are available upon request.

Storage Conditions
 Product shelf life has been proven through age testing up to 24 months under the following conditions :
 Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions