

T052 Universal Near Edge Wax

This excellent wax quality covers all general purpose requirements for near edge machines. It has been accredited for use within the food industry by ISEGA. It provides clear, crisp barcodes - standard, rotated or 2-D – on a variety of paper label stocks. The ink coating dissipates static and, coupled with the ribbon's low energy requirements, helps to prolong print head life.

General Item Data		
Film Thickness	:	4.5µm
Print Speed	:	12" = 300mm/s
Print Energy	:	Low - Medium

Substrate Application Range			
Vellum	✓	Tag Board	✓
Uncoated	✓	Matt Coated	✓
Semi Gloss	✓	Gloss Coated	✓

Characteristics Level										
Chemical Resistance	1	2	3	4	5	6	7	8	9	10
Durability	1	2	3	4	5	6	7	8	9	10
Substrate Versatility	1	2	3	4	5	6	7	8	9	10
Print Energy	1	2	3	4	5	6	7	8	9	10
Print Speed	1	2	3	4	5	6	7	8	9	10

Revision B

1 = Low 10 = High

These tests are performed using standard Pelikan test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.



Conforms to REACH (1907/2006/EC) RoHS (2011/65/EU) & WEEE 2002/96/EG). Material Safety Data Sheets are available upon request.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions :

Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions