



# Belcom

PR14316-1

## Low Loss Flexible Communication Coax 75Ω

High performance Low Loss range suitable for satellite , video applications – CCTV , CATV , baseband or broadband . Far more flexible than any corrugated solution

This versatile range is available in a number of sizes with FireFighter® Low Smoke Zero Halogen sheath according to IEC60332-3-24 as standard. PE sheathed and steel wire armoured versions are available on request.



**FireFighter**  
Fire Performance Cables

 01279 871129

 01279 871150

 [sales@belcom.co.uk](mailto:sales@belcom.co.uk)

 [www.belcom.co.uk](http://www.belcom.co.uk)

# Low Loss Flexible Communication Coax 75 $\Omega$

## Cable Guide



Coax Type		200	240	300	400	600
<b>Physical Characteristics</b>						
Inner Conductor		Solid plain copper	Solid plain copper	Solid plain copper	Solid plain copper	Solid CCA
Diameter	mm	0,60	0,80	1,15	1,65	2,74
Dielectric		Foam PE	Foam PE	Foam PE	Foam PE	Foam PE
Diameter	mm	2,80	3,65	5,10	7,20	11,56
Shield		Aluminium tape	Aluminium tape	Aluminium tape	Aluminium tape	Aluminium tape
Diameter	mm	2,90	3,75	5,20	7,30	11,71
Braid		TCWB	TCWB	TCWB	TCWB	TCWB
Diameter	mm	3,30	4,35	5,60	7,90	12,45
Outer Jacket		LSZH	LSZH	LSZH	LSZH	LSZH
Diameter	mm	4,50	6,00	6,80	10,10	14,99
<b>Part Number</b>						
LSZH FireFighter®		<a href="#">200754</a>	<a href="#">240754</a>	<a href="#">300754</a>	<a href="#">400754</a>	<a href="#">600754</a>

PE : Polyethylene

LSZH : Low Smoke Zero Halogen FireFighter®

TCWB : Tinned Copper Wire Braid

CCA: Copper Clad Aluminium