



## GUIDE TO ROTOWASH

### Standard Brush Life

The following guide is based on original Rotowash brushes only, and assumes correct and proper maintenance and care of the Rotowash brushes throughout their life:

- \* Proper cleaning after use.
- \* Regular rotation of front/back brushes to maintain even wear.
- \* Regular soaking overnight in upright position in buckets of warm water with mild detergent (fairy liquid) to straighten/soften bristles.

FLOOR TYPE	GUIDE IN HOURS
Aluminium Escalator Treads	100 - 120 hours
Checkerplate	140 - 180 hours
Carpet -	
0 - 2 mm pile	700 - 1000 hours
2 - 7 mm pile	1000 - 1200 hours
Smooth hard floors -	
Lino/Vinyl/Wood	650 - 750 hours
Resin, Aggressive Anti-slip Vinyl and Concrete	180 - 220 hours
Tiles -	
Ceramic/Quarry	280 - 320 hours
Anti-slip ceramic	220 - 240 hours
Studded/ Ribbed Rubber (including Buffing)	550 - 650 hours

Issued by:  
Rotowash International Technical Division



ISO 9001 / BS 5750 Part 2 - Certificate No. 5020

Rotowash Ltd.,  
7 Victory Business Centre, Fleming Way, Isleworth, Middlesex TW7 6DB  
Tel: 020 8847 4545 E-Mail: [cleanfloors@rotowash.com](mailto:cleanfloors@rotowash.com)  
Fax: 020 8569 7906 Website: [www.rotowash.com](http://www.rotowash.com)  
Vat Reg. No. 906 9158 06 Company Reg. No. 06160994