1 EU - Type Examination Certificate

2 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU

3 Certificate Number: ExVeritas 16 ATEX 0142X Issue: 1

4 Equipment: MK3 or B Gas Detector Head

5 Manufacturer: Oliver IGD Ltd (International Gas Detectors)

6 Address: Triton House, Crosby Street,
Stockport, SK2 6TS. UK

7 This equipment and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

8 ExVeritas, Notified Body number 2585 in accordance with Article 9 of the Council Directive 2014/34/EU of 26 February 2014, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to design and construction of equipment and protective systems for use in potentially explosive atmospheres given in Annex II to the Directive

9 Compliance with the applicable Essential Health and Safety Requirements has been assured by compliance with the following Standards and section 16 of this certificate:

EN 60079-0: 2012 EN 60079-1: 2014 EN 60079-31:2014

10 If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

11 This EU-Type Examination Certificate relates only to the design, construction, examination and tests of the specified equipment or protective system in accordance to the Directive 2014/34/EU. Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system. These are not covered by this certificate.

12 The marking of the equipment shall include the following:

Ex II 2 G Ex db IIC T* Gb

II 2 D Ex tb IIIC T* Db

Temperature class dependent upon ambient, see description.

On behalf of ExVeritas

S Clarke CEng MSc MIET
Certification Manager

UKAS PRODUCT CERTIFICATION

No. 8613

Schedule

13 Description of Equipment or Protective System

The gas detector heads consist of stainless steel body, insert and sintered element. The body and insert are connected by a threaded flamepath. The insert can only be removed by a bespoke tool. In addition, the threaded flamepath is sealed with cement. The sintered element is cemented into the insert. The rear of the body incorporates a cemented bushing assembly, this facilitates the passage of flying leads from inside to outside the enclosure. The flying leads are to be to be terminated in a suitably certified enclosure. The gas detector heads have a maximum power dissipation of 1 W.

Ex d IIC T6 Gb
Ex tb IIIC T85°C Db
$-20°C \leq T_{amb} \leq +40°C$

Ex d IIC T5 Gb
Ex tb IIIC T100°C Db
$-20°C \leq T_{amb} \leq +55°C$

14 Descriptive Documents

14.1 Associated Report and Certificate History:

Report Number	Cert Issue Date	Issue	Comment
EVL0822/A/3	2016.05.27	1	Initial issue of the Prime Certificate

14.2 Compliance Drawings:

Issue 0

Number	Date	Issue	Description
5116101	2016.04.19	1	MK3 & Type B pellistor Assy
3454001	2016.04.19	5	Pellistor Engraving Detail

Schedule

15 Conditions of Certification

15.1 Special Conditions for Safe Use

- The free end of the permanently connected cable shall be protected in accordance with IEC 60079-0:2011/EN 60079-0:2012 Clause 14.1.
- In accordance with IEC/EN 60079-1:2014 Annex C, the rear end of the bushing shall be protected by fitting into a suitably certified enclosure. In addition, the bushing shall not be subjected to torque during installation or operation.
- The product shall not be connected to portable equipment.
- The product shall be earthed in accordance with IEC 60079-0:2011/EN 60079-0:2012 Clause 15 when fitted to a suitably certified enclosure.
- The flameproof joints employed in the equipment are not intended to be repaired.

15.2 Conditions for Use
(Routine Tests)

- None

16 Essential Health and Safety Requirements
Essential Health and Safety Requirements are addressed by the standards listed in section 9 and where required the report listed in section 14.1

The manufacturer shall inform the Notified Body of any modifications to the design of the product described by this schedule.