

Floodline Leak Detection

Floodline Multi-8 8 Zone Detection Cable

The unique "Multi-Zone" construction of the Multi-8 - 8 Zone water sensitive cable allows up to eight separately reporting detection zones to be provided from one length of cable.

The zone changeover points along the cable are provided by either traditional Floodline 8-zone junction boxes or the Plug And Play system. The zones can be any length but the usual length is between 5 and 15metres.

The sensor can be wetted and dried any number of times provided the cable is not contaminated with a substance that permanently changes its electrical characteristics. If the contamination is soluble then the cable can be removed, washed (clean water only), dried and returned to use subject to the level of contamination.

Applications:

Below raised floors
Above suspended ceilings
Run in drip trays
Laid around the base of plant, apparatus or
tank
Laid in loops or wave pattern for general
monitoring of larger areas
Attached to pipework within lagging

Detection:

Activates with any conductive liquid anywhere along the entire length of the detection cable. Once dry can be returned to use

Construction:

A tough, all polymeric, low smoke and fume, zero halogen construction

Dimensions:

5mm Diameter

Fixing

For fixing to floor or other surface, use standard 6mm tower clips, self-adhesive clips or tie-wraps. Detection cable is laid loosely with special Caution Tags attached at regular intervals to identify zone.



E&OE 06r01

