

## Floodline Refrigerant Gas Sensor RGD1301



Gas detection:  
R407c  
R410A  
R134a  
R22

The Floodline RGD1301 Refrigerant Gas Sensor can be used as a stand-alone refrigerant alarm system OR be included as part of a larger water/oil leak detection system. It can also be used to provide a dedicated refrigerant gas detection alarm package.

The Floodline RGD1301 ensures companies comply with BS EN378 and detects refrigerant gases to HSE Occupational Exposure Limits.

BS EN378 specifies the installation of fixed refrigerant leak detectors in both existing and new systems of all sizes (with certain exceptions).

The Floodline RGD1301 sensors can be connected to a standard Floodline Control Panel giving additional audible and visual alarm features in addition to the facility for onward communication to BMS etc.

**Applications:**  
VRV Air Conditioning systems  
Refrigeration compressor packs  
Machine/Plant Rooms  
A/C Service Tunnels  
Hotel Bedrooms  
DX Split Units

**Detection:**  
Constant monitoring of the area for any build up of chosen refrigerant gases above a preset level – When a leak above the preset levels is detected, audio/visual warnings are given.

Audible & visual alarms also at central Floodline Control Panel.

**Construction:**  
ABS

**Dimensions:**  
H: 90mm x W: 160mm x D: 50mm

**Fixing:**

Wall/surface mounted at suitable height based on occupancy of room being monitored & refrigerant gas being detected.

**Operation:**

The Floodline RGD1301 can be preset to different modes of operation :

**Operational Modes:**

**Default Mode:** In “Leak Alarm” a warning is given by pulsing the 85dB sounder and flashing the “Status LED” red. The integral relay energises, the system remains in alarm until gas concentration falls below the preset level and the reset button is pressed.

**Sounder Disabled:** As per **Default Mode** but local audible alarm is disabled.

**Automatic Mode:** As per default mode but system resets automatically once concentration falls below the preset level.

**Specification:**

Supply: 3Watts at 12VDC OR 230VAC  
Relay Outputs: SPCO (3Amps @ 230VAC)  
Indicators: 3mm tri-colour LED  
Sounder: 85dB piezo



E&OE 13r01

