



CE

**R10** 

WARNING LIGHTING | DIRECTIONAL LIGHTING | LIGHTBARS | WHITE LIGHTING | REVERSING SAFETY



# ALARMS

## 800 Series OEM Mounting Pattern

Designed to meet all the harsh operational requirements of any fleets equipment, ECCO's 800 Series alarms feature a reverse-mounted speaker design and reinforced nylon housing providing unrivaled durability. These alarms are so robust that an ECCOLIFE<sup>™</sup> warranty covering the alarm for the life of the vehicle is offered on all models. These 800 Series alarm models feature a mounting bracket with the same mounting pattern popular with OEM's. Smart Alarm® models measure ambient noise and adjust their sound level, creating a volume that is safe without being annoying or contributing to noise pollution. Smart Alarms eliminate the need for constant manual adjustment and help prevent intentional alarm disconnection.


### Models

| PART NO. | TYPE  | VOLTAGE | dB(A)  | AMPS | APPROVALS                      |  |
|----------|-------|---------|--------|------|--------------------------------|--|
| 914N-001 | Smart | 12-24   | 87-112 | 1.5  | SAE Type F, CE, R10            |  |
| 876N-001 | -     | 12-36   | 112    | 1.3  | SAE Type A, CE, R10, UL, AMECA |  |

#### **Features and Benefits**

- Mounting backet features popular OEM footprint
- Reverse-mounted speaker enhances sound and protects the speaker from dust and moisture ingress
- · Reinforced nylon housing eliminates corrosion damage
- · Sealed in epoxy for protection against dust, moisture and vibration
- Temperature Range: -40°C to +85°C

#### **Dimensions**



#### **Alarm Specifications**

Connection: 16 AWG blunt cut wires Reinforced nylon housing Recommended mounting bolt: Bottom: 3/8-16 UNC Grade 5 or better Recommended washer: Bottom: 3/8" Type A Series N washer Recommended mounting torque: Bottom: 276 in. lbs.

+44 (0)113 237 5340 | sales@eccogroup.com

WWW.eccosafetygroup.com An ecco safety group™ Company