

# ECO-LINE BUNDED DIESEL STORAGE TANKS IDEAL FOR STORING AND DISPENSING FUEL SAFELY



RE-FUEL MACHINERY SAFELY AND EFFICIENTLY



10.000 LITRE DIESEL TANK WITH LOCKABLE CABINET



2.500 LITRE DIESEL TANK DISPENSING CABINET

#### **OVERVIEW**

The ECO-LINE diesel storage tank range provides exceptional value combined with superb build quality and a comprehensive list of features. These tanks have everything needed for storing and dispensing fuel safely and with minimum fuss.

#### **KEY FEATURES**

- Double walled rotationally moulded polyethylene diesel tank
- 110% bunded in accordance with regulations
- Lockable fuel dispensing cabinet
- Submersible pump Flow rate 70 litres/min
- Automatic nozzle & Nozzle holder with pump on/off switch
- 6 metre hose
- Digital flow meter displays the precise quantity of dispensed fuel
- Level gauge or wireless indicator
- 10 micron water and particulate filter
- 2" filling valve
- Bund alarm
- Overfill protection
- Inspection hatch
- Vents

#### PRODUCT CODES / PRICES

CAPACITY	110% BUNDED	CODE
1,500 LITRES	$\checkmark$	0007-315
2,500 LITRES	$\checkmark$	0007-325
5,000 LITRES	$\checkmark$	0007-350
7,500 LITRES	$\checkmark$	0007-375
10,000 LITRES	$\checkmark$	0007-390

#### **TECHNICAL DETAILS**


CAPACITY		WIDTH / LENGTH (MM)	HEIGHT (MM)	EMPTY WEIGHT (KG)	FULL WEIGHT (KG)	HOSE LENGTH (M)
1,500 LITRES	(330 GALLONS)	1,358	1,950	155	1,431	6
2,500 LITRES	(550 GALLONS)	1,708	1,990	180	2,307	6
5,000 LITRES	(1,100 GALLONS)	2,318	2,060	350	4,604	6
7,500 LITRES	(1,650 GALLONS)	2,550 / 2500	3310	520	7,071	6
10,000 LITRES	(2,200 GALLONS)	2,550 / 3,000	3,310	690	9,198	6

ALL APPROPRIATE CARE HAS BEEN TAKEN TO RECORD ACCURATE TECHNICAL DETAILS ABOVE - HOWEVER ALL WEIGHTS AND MEASUREMENTS SHOULD BE CONSIDERED APPROXIMATE



DISPENSING CABINET FOR 1,500, 2,500 AND 5,000 LITRE STORAGE TANKS

## STANDARD COLOUR:





### STANDARD SPECIFICATION

- Submersible pump Flow rate 70 litres/min
- Digital flow meter
- 6 metre hose
- Automatic nozzle

#### Important:

Before ordering this product we recommend you confirm with your fuel supplier what their minimum delivery amount is, and if any surcharges apply. This will help to determine the correct capacity of tank for your requirements.

# ECO-LINE ADBLUE STORAGE TANKS A COMPLETE STORAGE AND DISPENSING SYSTEM FOR ADBLUE



DURABLE ROTO-MOULDED POLYETHYLENE CONSTRUCTION





**LOCKABLE CABINET WITH HINGED DOOR** 

TANK DISPENSING CABINET

IMAGES FOR ILLUSTRATION PURPOSES ONLY - SMALL VARIATIONS MAY OCCUR

#### **OVERVIEW**

A complete storage and dispensing system for AdBlue, comprising of a fully bunded tank, 2" TODO fill point coupling and complete dispensing system including digital flow meter. Once in position and connected to mains electric supply the tank and dispensing equipment are ready for use.

#### **KEY FEATURES**

- 110% Fully bunded, tank-within-a-tank design
- Durable roto-moulded polyethylene construction
- Fully compliant with storage regulations
- Quiet, reliable and high-flow 35 litre/min 230v submersible pump
- Automatic shut-off dispensing nozzle
- 6 metre hose
- Digital flow meter displays the precise quantity of dispensed fuel
- Rotary tank contents gauge
- 2" filling point TODO
- Overfill protection
- Inspection hatch, 440mm
- Vents

#### PRODUCT CODES / PRICES

CAPACITY	110% BUNDED	CODE
1,500 LITRES	$\checkmark$	0007-115
2,500 LITRES	$\checkmark$	0007-125
5,000 LITRES	$\checkmark$	0007-150

#### **TECHNICAL DETAILS**

CAPACITY		WIDTH / LENGTH (MM)	HEIGHT (MM)	EMPTY WEIGHT (KG)	FULL WEIGHT (KG)	HOSE LENGTH (M)
1,500 LITRES	(330 GALLONS)	1,358	1,950	155	1,790	6
2,500 LITRES	(550 GALLONS)	1,708	1,990	180	2,905	6
5,000 LITRES	(1,100 GALLONS)	2,318	2,060	350	5,800	6

ALL APPROPRIATE CARE HAS BEEN TAKEN TO RECORD ACCURATE TECHNICAL DETAILS ABOVE - HOWEVER ALL WEIGHTS AND MEASUREMENTS SHOULD BE CONSIDERED APPROXIMATE



#### **STANDARD COLOUR:**



DISPENSING CABINET FOR 1,500, 2,500 AND 5,000 LITRE STORAGE TANKS

IMAGES FOR ILLUSTRATION PURPOSES ONLY - SMALL VARIATIONS MAY OCCUR

## STANDARD SPECIFICATION

- ▶ Submersible pump Flow rate 35 litres/min
- Digital flow meter
- ▶ 6 metre hose
- Automatic shut off dispensing nozzle

#### Important:

Before ordering this product we recommend you confirm with your fuel supplier what their minimum delivery amount is, and if any surcharges apply. This will help to determine the correct capacity of tank for your requirements.

# PRO-LINE ADBLUE STORAGE TANKS A COMPLETE STORAGE AND DISPENSING SYSTEM FOR ADBLUE



FULL HEIGHT CABINET FOR EASY ACCESS TO DISPENSING EQUIPMENT







FRONT VIEW OF 10.000 LITRE TANK

#### **OVERVIEW**

A complete storage and dispensing system for AdBlue, comprising of a fully bunded tank, 2" TODO fill point coupling, full height cabinet for easy access to dispensing equipment, electronic level monitoring system and complete dispensing system including digital flow meter. Once in position and connected to mains electric supply the tank and dispensing equipment are ready for use.

#### **KEY FEATURES**

- 110% Fully bunded, tank-within-a-tank design
- Durable roto-moulded polyethylene construction
- Full height cabinet for easy access to dispensing equipment
- 35 litre/min 230v submersible pump
- Automatic shut-off dispensing nozzle
- 6 metre hose
- LIPREMOS level monitoring system
- Maximum level alarm
- 2" filling point TODO
- Overfill protection
- Inspection hatch, 600mm
- Vents

#### PRODUCT CODES / PRICES

CAPACITY	110% BUNDED	CODE
3,500 LITRES	$\checkmark$	0007-235
5,000 LITRES	$\checkmark$	0007-250
7,500 LITRES	$\checkmark$	0007-275
10,000 LITRES	$\checkmark$	0007-290

#### **TECHNICAL DETAILS**

CAPACITY		WIDTH / LENGTH (MM)	HEIGHT (MM)	EMPTY WEIGHT (KG)	FULL WEIGHT (KG)	HOSE LENGTH (M)
3,500 LITRES	(770 GALLONS)	2,130 / 2,870	2,100	265	4,080	6
5,000 LITRES	(1,100 GALLONS)	2,360 / 3,100	2,100	350	5,800	6
7,500 LITRES	(1,650 GALLONS)	2,550 / 3,310	2,500	520	8,695	6
10,000 LITRES	(2,200 GALLONS)	2,550 / 3,310	3,000	690	11,590	6

ALL APPROPRIATE CARE HAS BEEN TAKEN TO RECORD ACCURATE TECHNICAL DETAILS ABOVE - HOWEVER ALL WEIGHTS AND MEASUREMENTS SHOULD BE CONSIDERED APPROXIMATE



**STANDARD COLOUR:** 



#### STANDARD SPECIFICATION

- > 35 litre/min 230v submersible pump
- ▶ LIPREMOS level monitoring system
- ▶ 6 metre hose
- Automatic shut off dispensing nozzle

#### Important:

Before ordering this product we recommend you confirm with your fuel supplier what their minimum delivery amount is, and if any surcharges apply. This will help to determine the correct capacity of tank for your requirements.

# FIGI Proof

FUEL PROOF LTD

TEL: +44 (0) 1524 850685

MIDDLETON BUSINESS PARK
FAX: +44 (0) 1524 850685

MIDDLETON ROAD
WEB: WWW.FUELPROOF.CO.UK

HEYSHAM
E-MAIL: INFO@FUELPROOF.CO.UK

LA3 3FH