







This is a low cost integrated single skin steel partition system suitable for a wide range of applications, including industrial offices, storage areas, factory dividing walls. A comprehensive range of single and double swinging doors, sliding doors and hatches are available. These can be fitted with most types of locks and latches, including interlocks.

The panels are bolted together using M8 bolts and nuts, the panels are also fixed to the floor with pan head screws and 6mm plastic plugs. Posts are used every third panel and are fixed to the floor with 12mm anchor bolts and in-fills come as 21 SWG CR4 sheet steel or 50mm x 50mm x 12SWG weld mesh.

Technical Information	
Standard Panel Heights:	2440mm and 3050mm
Standard Panel Widths:	1220mm, 1000mm, 915mm, 610mm and 305mm
Dado Height:	1220mm
Single Doors:	1980mm high x 915mm wide
Double Doors:	1980mm wide x 1806mm wide
Welded Mesh Sheet:	50mm x 50mm x 12 SWG
Windows:	Up to 6.4mm glass set in plastic glazing bead
Posts – 2 Way	80mm x 40mm x 3mm
Posts – 3 Way & Corner:	80mm x 40mm x 3 mm
Standard Paint Finishes:	Yellow RAL 1018, Grey BS00A05 And Sandstone BS08B17
Construction:	Cold rolled mild steel angle and cold rolled tees with sheet steel or welded mesh infill sheets spot welded together

Billington Safety Systems Ltd. 42 Regency Road, Brampton Bierlow, Rotherham, S63 6GF Tel: 01709 873903

Web: www.billingtonsafetysystems.co.uk Email: sales@billingtonsafetysystems.co.uk